TR-CI-937

3590

AROD-7875.1-RT

AD 710 363

3580

20090504 298

NOTATION OF MOVEMENT

FINAL REPORT

GRANT

DA-ARO-D-31-124-G998

Sponsored by

U.S. ARMY RESEARCH OFFICE-DURHAM

15 February 1970

DEPARTMENT OF ELECTRICAL ENGINEERING
UNIVERSITY OF ILLINOIS
URBANA, ILLINOIS
61801

Reproduced by the
CLEARINGHOUSE
for Federal Scientific & Technical
Information Springfield Va. 22151

This document has been approved for public release and sale; its distribution is unlimited. The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

183

NOTATION OF MOVEMENT

FINAL REPORT

Covering the Period

1 March 1968 - 31 August 1969

GRANT

DA-ARO-D-31-124-G998

Sponsored by

U.S. ARMY RESEARCH OFFICE-DURHAM

Issued

15 February 1970

DEPARTMENT OF ELECTRICAL ENGINEERING
UNIVERSITY OF ILLINOIS
URBANA, ILLINOIS
61801

BLANK PAGE

PREFACE

Kraepelin (1) in his monumental attempt to develop a taxonomy of mental disorders was the first to use the notion of "sensorium" as the totality of the faculties of perception, orientation, memory, etc., as distinct from those of reasoning, volition, affectivity, etc. The conditions of the sensorium being clouded or else clear, other circumstances alike, allows for powerful diagnostic discrimination, hence provides an important conceptual tool to determine etiology and, ultimately, therapy of the disorder.

Complementary to this notion, the notion of "motorium" will be introduced here as the totality of the faculties of voluntary controlled movements from gait to speech to writing, etc., as distinct from those controlled by the Sympathicus, heart beat, peristalsis, papillary dilation, etc.

Phylogenetically, of course, sensorium and motorium evolve interdependently and synchronously, putting the question of primacy into the realm of disputes on the primacy of egg or chicken.

While many quarters still hold to the Cartesian notion that the so called "higher mental functions" emerge from the sensorium, it has become today abundantly clear that early impediments of the motorium afflict the sensorium as much as impediments of the sensorium leave their mark on the motorium. Epistemologically, even such abstract notions as "affirmative"

or "negative" (2), and as "true" or "false" (3), can be shown to be coupled to elementary movements respectively as approach or withdrawal, and as the proper or improper execution of a conditioned reflex. Consequently, the preoccupation with the study of the sensorium appears to have purely historical roots, and the maintained distinction between "sensory" and "muscle" physiologists is indeed not designed to foster an integrated vision of motorium and sensorium. Exceptions are, of course, Eccles' recent work on the cerebellum (4) and Green's elegant views on controlled and smoothed purposive movements (5).

Probably, the first to take qualitative studies of the motorium seriously were Noa Eshkol and Abraham Wachmann who, during the 1950's, developed a notation of movement (6) which was intended to prescribe by appropriate concatenations of symbols taken from a finite alphabet all movements that can conceivably be executed by the human body and, conversely, to describe any such movement by a corresponding string of symbols.

While it is obvious that any symbolism to be developed for this purpose will make use of the intrinsic constraints of bodily movements, it is, however, not obvious whether or not the symbols chosen for the alphabet as well as the chosen rules of concatenating symbols are necessary and sufficient to serve the task at hand. In other words, the question of completeness and consistency of a descriptive formalism for

bodily movements is by no means trivial, for nothing less is required than to show isomorphism between potential movements and the syntax of their symbolic representations.

On the other hand it is clear that such a system of notation would be of considerable value not only as a nucleus for a future theory of the neurophysiology, biomechanics and biology of organic movement, but also by its immediate applicability to the construction of anthropomorphic automata which are to perform in environments inaccessible or hostile to a human operator, and with which communication is maintained via channels of capacities orders of magnitude below those needed for continuous surveillance and without the benefits inherent in the redundancies of symbolic discourse.

At the time of the initiation of this project it was established that the alphabet earlier developed by Eshkol and Wachmann is indeed sufficient to satisfy the condition of completeness, however, the difficult task of showing consistency was not yet approached. Moreover, the formalism so far developed left on the syntactic level much to be desired.

To overcome these difficulties, the approach chosen in this study was to transcribe Eshkol-Wachmann notation into a computer program which would allow the machine to execute the movements by computing its trajectories, and deliver these either in numeric or graphic form. From this exercise the following results were anticipated:

1. A check of consistency of the underlying notation. Inconsistencies would immediately result in rejects of the program.

2. On the command side (input), the syntax of the programming language would provide the bridge between a command given in (somewhat restricted) natural language and in Eshkol-Wachmann notation.
3. On the execution side (output) it would provide a complete system of kinematic descriptions of movement, providing an invaluable formal skeleton for the study of dynamic and purposeful behavior.

The following report is a brief summary of the work performed under the auspices of this Grant, and it is believed that the desired results have been achieved. The notation has been found to be consistent; any command can be executed by the machine; and the initial steps of a mathematical foundation for a dynamic study have been made by extending the kinematic algorithm developed in this study. It is felt that the most excruciating and exhausting phases of any such attempt have been overcome and that the results presented herein will serve as a convenient basis for further rigorous quantitative and qualitative studies of man's dynamic potential.

The participants in this program acknowledge with gratitude the perpetual cooperation of the Departments of Electrical Engineering and of Computer Science, and particularly of the Department of Physical Education for Women, whose head, Dr. Alyse T. Cheska was an untiring source of encouragement and help.

I wish to express my thanks to Miss Janet Ficken, Mrs. Alexis Peterson and Miss Faith Pukszta for their invaluable contributions in organizing and executing this report.

H.V.F.

REFERENCES

1. Kraepelin, E., Psychiatrie, 2nd edition, Abel, Leipzig (1887).

2. Von Foerster, H., "Thoughts and Notes on Cognition" in Cognition - A Multiple View, P. Garvin (ed.), Spartan Books, New York (in press).

3. Langer, S., Philosophy in a New Key, New American Library, New York (1951).

4. Eccles, J. C., M. Ito, and J. Szentagothai, The Cerebellum as a Neuronal Machine, Springer-Verlag, New York (1967).

5. Greene, P. H., "New Problems in Adaptive Control" in Computer and Information Sciences, J. T. Tou and R.H. Wilcox, Spartan Books, Washington, D. C. (1964).

6. Eshkol, N. and A. Wachmann, Movement Notation, Weidenfeld and Nicolson, London (1958).

PERSONNEL

Principal Investigator -

HEINZ VON FOERSTER
Professor, Departments of Biophysics
and of Electrical Engineering

Visiting Research Assistant Professor -

NOA ESHKOL
Professor, Israel Music Institute, Israel

Research Assistants -

PETER MELVIN
Department of Astronomy

JEAN MICHL
Department of Computer Science

Consultants -

ILANA BANAI
Movement Notation Society, Israel

"
HERBERT BRÜN
Professor, Department of Music

JOHN HARRIES
Movement Notation Society, Israel

LAURA HUELSTER
Professor, Department of Physical Education

RACHEL NUL
Movement Notation Society, Israel

ABRAHAM WACHMANN
Professor, Israel Music Institute, Israel

SHMUEL ZEIDEL
Movement Notation Society, Israel

Clerical -

JANET FICKEN
Biological Computer Laboratory

ALEXIS PETERSON
Biological Computer Laboratory

TABLE OF CONTENTS

PREFACE.....iii

PART A. THE PRINCIPLES OF MOVEMENT NOTATION.....3

I. The Body and the Manuscript Page.....8

II. The System of Reference.....10

III. The Individual Systems and the General System of Reference.....15

IV. Zero Position - Front.....17

V. Positions.....20

VI. The Notation of Movement: The Type of Movement.....24

VII. The Notation of Movement: Spatial Definition and Sense of Movement.....24

VIII. The Notation of Movement: Amount of Movement.....36

IX. Simultaneous Movement.....39

X. The Weight.....41

XI. Contact.....43

XII. Front.....44

XIII. Conventions.....46

PART B. MACHINE REPRESENTATIONS OF MOVEMENTS.....53

I. Physiology of movement.....54

II. Mathematical Abstraction of the Human Body.....56

III. The E-W Program: DANCER.....62

Page

IV. A Model of the Human Body: STKMAN.....84

V. Conclusion.....94

References.....98

Appendices.....99

PART A

THE PRINCIPLES OF MOVEMENT NOTATION

(Eshkol and Wachmann)

BLANK PAGE

THE PRINCIPLES OF MOVEMENT NOTATION

The progress of human thought and activity in various fields in science and in art without the development of appropriate notations is unimaginable. As in other spheres, movement of the human body requires a concise and simple system of symbols which will make possible composition and description of events in this field; such a system should constitute a tool of communication by means of which three aims are attainable:

1) The recording of movement.
2) The possibility of analysis of, and composition in, the material (movement).
3) The creation of common concepts among the workers in the field under discussion, making possible clarification and definition, tuition and criticism.

By trying to imagine the development of the world of music without a musical notation, we may obtain an idea of what the notation could contribute to the world of movement in all its various branches.

In order that the notation system may be efficient and valid, and capable of develcping the treatment of the world of movement without arriving at internal contradictions, it must be founded on a basic analysis (without a priori conventions) of all the components of the movement of human body that can be perceived.

If the notation is to constitute a symbolic system presenting the components of the material and the relations between them in the most exact manner, it must be so constructed that the manipulations possible within it do not fall short of the manipulations possible in the material itself. In other words, the test of the notation lies in its making possible the expression (in principle, and without going into detail) of the maximum of movement possibilites of the human body. Only then does there exist the probability that every movement open to perception will be expressible in the notation.

The more fundamental the component, the more simple and efficient must be its expression in the notation. When entering upon greater detail, and aspects of secondary importance, greater freedom in the introduction of conventions becomes permissible.

In the movement notation, the following aspects are given symbolic expression:

1) The human body.
2) The movements of the parts of the body.
3) Movement space (system of reference - sense of movement - observer).
4) Quantitative data (amount of movement, duration).
5) Conventions.

1) The Human Body. For the purposes of the notation we regard the human body as a system of straight "rods" (limbs)

connected to one another by joints. Movement of the whole body is therefore the sum of the movements of the separate limbs, just as a particular state of rest of the whole body is the aggregate of the positions of the separate limbs.

2) The Movement of the Parts of the Body. In analysing the movement of the body, we shall begin with the analysis of the movement of a single limb. Each limb moves about the joint to which it is connected. In this movement (assuming that the limb possesses complete freedom of movement about the joint) three elements are discernible:

a) The centre of movement (the joint).

b) The axis of the limb.

c) The axis of movement.

If the joint is considered as a centre of movement fixed in space, then clearly every movement of the limb about it is in fact "spherical" (takes place within a sphere).

In the whole of "spherical" movement, three "types" may be distinguished (different groups of relations between the axis of the limb and the axis of movement):

Rotatory movement, in which the limb moves about its own axis without changing its place in space. The axis of the limb and the axis of movement coincide. (The extremity of the limb remains fixed at one point on the surface of the sphere.)

Plane movement, in which the limb moves in a plane. The axis of the limb is at right angles to the axis of

movement. (The extremity of the limb describes the "great circle" on the surface of a sphere.)

Conical movement, in which the limb moves in a cone. The axis of the limb is at an acute angle to the axis of movement. (The extremity of the limb moves in a circle which is smaller than the "great circle".)

3) Movement Space. For the description both of positions and of movements, a system of spatial reference is required to which can be related the place of the limb, its change of place (movement) and the sense (direction) of movement. Since the system of movement of the body is a system of spheres, i.e., rods moving about joints, the system of reference chosen is a system of spherical coordinates to which is related in parallel fashion the "movement sphere" of each separate limb.

The relation to this system of reference, positions may be established and indicated by giving to each limb the symbols for the spatial coordinates appropriate to its position. However, movement may be described in three ways:

1) By expressing the movement as a transition from one defined position to another defined position (indicating the character of the path, sense, amount of movement, and duration).
2) By establishing the positions of the axis of the limb and the axis of movement (plus sense, amount and duration).
3) By reducing the path of the movement to two projections: the projection on the horizontal plane,

and the projection on a vertical plane. The simultaneous description of these two projections defines the path of the movement (plus sense, amount and duration).

Every movement of a limb in a particular path can be executed in one of two contrary directions: "clockwise" or "anti-clockwise" (positive or negative). It is essential to establish which is to be the "positive" and which the "negative" sense in the different types of movement.

4) Quantitative Data. Having defined type and path of movement, and sense, two further quantitative data are still required for the full writing of movement: "amount of movement" and "duration of movement".

It is necessary to indicate the size of the sector of movement performed by the limb in the given path. Since we are concerned with circular paths, the movement sector can be measured as a fraction or as a multiple of a circle.

The duration of each movement must be indicated on the manuscript page. It is expressed as a multiple of a time unit, the value of which is established for each particular piece of notated work, taking into consideration the structure of its time pattern.

5) Conventional Signs. In addition to the basic factors of movement, there are certain physical phenomena without the description of which movement cannot be accurately expressed. In such cases, and in cases where a movement recurs with

great frequency, it is possible and desirable, for reasons of simplicity, to employ special symbols and abbreviations. A list of these signs and abbreviations is given on pages 46-49.

I. THE BODY AND THE MANUSCRIPT PAGE

Figure 2 shows the division of the body into independently moving parts. To each of these limbs a space is allocated on the manuscript page (Figure 1). For certain styles of movement, the body may be understood as comprised of more moving limbs than are provided for here (by the addition of fingers, for example). In such cases, the required number of spaces is added to the manuscript page. On the other hand, in the case of movement confined to a smaller number of limbs the page need include only the spaces necessary, as is done in a musical score.

Figure 2 shows the division of the manuscript page: each of the upper 18 horizontal spaces is allocated to a different limb. The bottom space is allocated to the notation of the "front" (see illustrations on page 21). The second space from the bottom is allocated to the notation of the weight and changes of weight (see illustrations on page 42).

The division of the page into equal vertical columns serves for the notation of the duration of the movements, each column representing a time unit whose absolute value is given at the beginning of the work (like the metronome indication in music). For example: TU = 78.



Figure 1.

Figure 2.

II. THE SYSTEM OF REFERENCE

When a limb moves about a "fixed" joint, the "surface" or "paths" produced by its movement are confined within an imaginary sphere. The extremity of the limb moves on the surface of the sphere. (See Figure 3.)

A system of reference appropriate to the analysis of positions or movements of a limb moving "within a sphere", is a spherical system. The definition and measurement of positions and movements within such a system are made possible by the spatial division of the sphere by means of two complementary systems (see Figure 4),

a) the network of the coordinates on the surface of the sphere (see Figure 5), and

b) the dispersion of the "positions", i.e., the lines connecting the centre of the sphere and the points of the network of coordinates (see Figure 6).

The network of coordinates dividing the surface of the sphere is constructed (like the geographical globe) from an intersecting net of "lines of longitude" (vertical circles) and "lines of latitude" (horizontal circles), the intersections of which are the points of the coordinate network. The axis connecting the upper and lower poles always remains in the vertical position, and is called "the vertical axis of the system of reference". The "equatorial plane" always remains in the horizontal position, and is called "the horizontal plane of the system of reference".



Figure 3.



Figure 4.



Figure 5.



Figure 6.

By the term unit of measure of the system of reference we refer to the distance between two adjacent points of the network or between two corresponding positions (see Figure 7); an angular unit (arc or sector), measured in degrees of a circle. In this section we deal with a division in which the lines of longitude and of latitude are both divided by the same unit, so that the angular distance between any two adjacent points of the network is equal in the vertical and the horizontal directions. The unit of measure may,however, be of different size, according to need. Figures 8, 9, and 10 show a schematic skeleton of the system of reference, with a different unit of measure in each case. In Figure 8 the unit of measure is 90°, in Figure 9, 45° and in Figure 10, 30°.

The number of lines of longitude and latitude will change correspondingly to the size of the unit of measure, and also, as a direct result of this, the number of positions. The size of the unit of measure determines the quantitative scale of the system of reference, and at the beginning of each manuscript, the equivalent is given (in degrees) of one unit of measure in the chosen scale. Every line of longitude is indicated by a number. If we establish one of the directions on the horizontal plane as "horizontal zero", then the number expressing any given line of longitude will indicate by how many units of measure it deviated, horizontally, from direction 0.



Figure 7.



Figure 8.



Figure 9.



Figure 10.

Every position of the coordinate network may be expressed by two numbers. One number indicates on which line of longitude it is located (the "horizontal component"). The other number indicates its place on the said line of longitude (its latitude); that is--by how much the said point deviates vertically from the lower pole (point 0).

For the expression of a network-point or position, two numbers are necessary, placed one above the other and enclosed in brackets, for example, $\binom{3}{2}$. The lower number represents the horizontal component, and the upper the vertical component.

In Figure 11 a number of movement sectors are enclosed within the system of reference, 1) a horizontal plane movement sector between positions A and B, 2) a vertical plane movement sector between positions E and F, 3) an intermediate plane movement between positions C and D, and 4) a conical movement between positions G and H. (An exact definition and explanation of the above types of movement is given later.)

III. THE INDIVIDUAL SYSTEMS AND THE GENERAL SYSTEM OF REFERENCE

The construction of the system of reference has so far been related to a single limb. Movement of the whole body is the aggregate of the movements of the various limbs. The analysis of movement of the whole body is thus the analysis of the movement of each separate limb in relation to its own



Figure 11.

"individual" spherical system of reference, the centre of which coincides with the joint about which that limb moves. Since the individual systems of reference are in parallel relation to each other, instead of speaking of a cluster of parallel spherical systems, we may speak of a single imaginary spherical system: the System of Reference. Figure 12 demonstrates this parallelism. In Figure 13 the individual system of reference attached to a particular limb (in this case, the forearm) is carried with it, in its movement. In Figure 14 a section of horizontal movement of the arm (with A' - B' included in its individual sphere and A - B the same movement reflected in a second system) is shown.

IV. ZERO POSITION - FRONT

In the writing both of movement and of positions, we take into consideration the longitudinal axis of the limb. To determine the position of a particular limb means determining the place of its longitudinal axis; and the analysis of its movement means the analysis of the movement of its axis (see Figure 15). The position of the body in normal upright posture, with feet parallel, is referred to as <u>zero position</u>. The figure brings out the fact that in zero position most of the limbs are in a vertical position. When a limb is in zero position, this is indicated by the sign (0) in the appropriate space.



Figure 12.



Figure 13.



Figure 14.

In zero position the "forward" surfaces of all the limbs of the body face in the direction (0) on the horizontal plane, and both together face the observer; this state is expressed by the sign 0 in the lowest space of the page--the space allocated to the "front" (see Figure 16).

V. POSITIONS

The position of the body at a particular moment is the sum of the positions of all its parts at that moment. In order to notate a position of the whole body, these simultaneous states must be expressed. One example of such notation was that of "zero position", which was first defined, and then given a conventional sign. In all other cases, however, it is necessary to define the position of each limb in space. In analysing and writing the position of a limb, we relate it to that position in the system of reference which is parallel to the axis of the limb. In Figure 17, the diagram is given again here, to show the positions and their symbols, as defined in a system of reference with the scale of 45°. Figure 18 shows the definition of positions of the forearm. Each position is defined by two numbers in brackets; the lower indicates the horizontal coordinate, and the upper, the vertical coordinate. The position of the whole body is represented in a vertical column, the position of each limb being written in the appropriate space in Figure 19.

Figure 15.



Figure 16.



Figure 17.



Figure 18.





Figure 19.

VI. THE NOTATION OF MOVEMENT: THE TYPES OF MOVEMENT

One type of movement is rotatory movement with angle of movement zero. (The term "angle of movement" is given to the angle obtaining between the axis of the limb and the axis of movement through the movement.) The axis of the limb and the axis of movement coincide as shown in Figure 20. Rotatory movement in various limbs is apparent in Figure 21.

A second type of movement is conical movement, with angle of movement less than 90°. The axis of the moving limb produces a conical envelope, or part of such an envelope (see Figure 22). Shown in Figure 23 are conical envelopes produced by the movements of the arm and of the leg. The two cones produced by the arms have different angles of movement.

A third movement is plane movement which has an angle of movement of 90°. In Figure 24 the movement of the axis of the limb produces a plane; and in Figure 25, plane movement in the arm and the leg is pictured.

VII. THE NOTATION OF MOVEMENT: SPATIAL DEFINITION AND SENSE OF MOVEMENT

7.1 Rotatory Movement.

In rotatory movement the sense ("direction") of movement is determined in relation to zero position (Figure 26). In zero position almost all the limbs are in a vertical position,



Figure 20.



Figure 21.



Figure 22.



Figure 23.



Figure 24.

Figure 25.

and rotatory movement in that position is performed about the vertical axis; any rotation in a clockwise direction, as seen from above, is in the positive sense; rotation in the anti-clockwise direction is in the negative sense. These senses of rotatory movement remain "attached" to the limbs, even when the latter change their location in space (Figure 27). The arrows in the figure show the direction of rotatory movement in the positive sense. The sign for positive rotatory movement is ⌒. The sign for negative rotatory movement is ⌣.

[Note: The "rotatory state" of the limb is indicated by allotting to the four sides of the limb (left, right, front, and back) the appropriate numbers, derived from a system of reference of scale 1 = 45°. These numbers remain attached to the sides of the limb, like "labels". (Note that, even in bilaterally symmetrical limbs, this labelling is not bilateral.) It is then possible to indicate at any moment which side of the limb faces upward, excepting in positions $\binom{0}{0}$ and $\binom{4}{0}$, in which cases the side facing direction (0) is indicated.]

7.2 Conical Movement.

The size and location of a cone produced by a moving limb are defined with the aid of the positions of the ends of the diameter of the base of the cone. As the position of the limb at the beginning of the movement may be taken as one of the ends of the diameter, only the position of the other end



Figure 26.



Figure 27

need be indicated. (See Figure 28.) In conical movement the sense of movement is determined by looking from the apex of the cone towards the base: the movement then seen as clockwise is positive, and that seen as anti-clockwise is negative. In Figure 28, the movements in the left-hand and upper cones, in the direction indicated by the arrows, are in negative sense; that in the right-hand cone, in the direction of the arrows, is positive. The sign for positive conical movement is $\wedge$. The sign for negative conical movement is $\vee$.

7.3 Horizontal Plane Movement.

Horizontal plane movement is movement in which the limb is in a position parallel to the ground at the beginning of the movement and moves on the horizontal plane. (See Figures 27-30.) The sense of movement in horizontal plane movement is established by looking down on the plane from above:

Positive movement - clockwise: →

Negative movement - anticlockwise: ←

In Figure 30, the horizontal plane movement from A to B is positive and from B to A negative.

7.4 Vertical Plane Movement.

Vertical plane movement is movement in which the axis of the limb moves in a vertical plane. (See Figure 31.) A limb may move in a vertical plane movement from any position in the system of reference. In such movement, the positive



Figure 28.



Figure 29.



Figure 30.

sense is the direction upward from $\binom{0}{0}$, in the given plane. The opposite direction in the same plane is the negative sense.

To notate vertical plane movement, it is necessary to indicate:

a) in which plane the limb moves

b) the sense of movement in that plane.

Positive vertical plane movement is written ↑. Negative vertical plane movement is written ↓.

In Figure 32 the movement from A to B in plane (2), and from A' to B' in plane (7) is in the positive sense: (2)↑, (7) ↑. The movement from B to A in plane (2), and from B' to A' in plane (7) is in negative sense.

7.5 Intermediate Plane Movement.

Intermediate plane movement is movement in a plane tilted towards the horizontal plane. A limb can move in intermediate plane movement from any position excepting the vertically upward or downward positions (from which the only plane movement that can be performed is vertical plane movement.) (See Figure 33.)

Since intermediate plane movement is composed of two components--horizontal shift and vertical shift--four combinations of sense are therefore possible:

1) Positive horizontal component + positive vertical component; in the figure, from E to F. Symbol: ↗



Figure 31.



Figure 32.



Figure 33.

2) Positive horizontal component + negative vertical component; in the figure, from A to B. Symbol: ↘

3) Negative horizontal component + positive vertical component; in the figure, from B to A. Symbol: ↖

4) Negative horizontal component + negative vertical component; in the figure, from F to E. Symbol: ↙

N.B. In the present book, the following convention is used in writing intermediate planes: the symbol $(\overset{3}{\underset{2}{\mapsto}})$ for example, indicates movement in an intermediate plane in the positive sense from a given starting position, to the position written above the flighted arrow. The movement may be continued in the same plane according to an amount of movement appended: e.g., $(\overset{3}{\underset{2}{\mapsto}})$ 8.

VIII. THE NOTATION OF MOVEMENT: AMOUNT OF MOVEMENT

All the types of movement enumerated, being circular, are movements which may complete circles of 360°. Any movement performed, then, completes either a whole circle, or part of a circle, or a number of circles. The amount of movement thus expresses the size of the path (movement sector) which the limb in fact performs. In rotatory movement the amount of movement is that part of a complete rotation or the number of rotations performed by the limb. In plane movement the amount of movement is the size of the circular plane sector

of the movement of the limb. In conical movement the amount of movement is that part of the conical envelope produced by the movement; or in other words the size of the arc passed through by the extremity of the limb in its movement at the base of the cone.

The units of measurement of movement are the same units used in the construction of the coordinative network of the system of reference, since we assume that movements are performed between the points of the network. In rotatory movement the amount of movement is indicated by a numeral expressing the number of units of measure, attached to the movement sign. For example, a rotatory movement with the amount of two units (a movement of 90° when the basic unit is 45°) is written $\overset{\frown}{2}$. In horizontal and vertical plane movement the amount is indicated by attaching the numeral to the arrow: on the right in vertical plane movement and above in horizontal plane movement: $\uparrow 2$ $\downarrow 2$ $\underset{\rightarrow}{2}$ $\underset{\leftarrow}{2}$. In intermediate plane movement the notation of the movement is divided between two numbers: one, written <u>beneath</u> the movement sign, expresses the amount of horizontal projection (shift) of the movement. The other, written <u>above</u> the movement sign, expresses the amount of the vertical projection (shift) of the movement. For example: $\frac{2}{2}\nearrow$. In conical movement the amount of movement is added at the right side of the movement symbol. For example: $\wedge 2$. Figure 34 provides an example of movement sectors in full notation - the path and its reverse.



Figure 34.

IX. SIMULTANEOUS MOVEMENT

In Figures 35-36, in every movement performed by the body (other than the extreme outer limbs), two kinds of limbs take part: the actively moving limb (the "heavy" limb), and all those limbs carried by it (the "light" limbs).

The light limbs, carried by the heavy limb, change their location in space as the result of the movement of the heavy limb. (See Figure 35, in which the torso is "heavy" and all the upper parts of the body are "light".) In this case, only the movement of the light limbs is written. However, independent movement of the light limbs is possible while they are being carried by the heavy limb, and the change of location of each of them in space is then a result of the simultaneous movement of the heavy limb plus the movement of the light limb (see Figure 36). In this case the movement of each limb is written in its space.

Situations are possible, in which we are concerned to retain a given position in the light limb relative to the system of reference, while it is carried passively by the heavy limb. In these situations, the symbol f is attached to the notated position of the light limb. When the sign f is attached to a movement sign, this signifies that the path of the movement of the light limb is not modified by the movement of the heavy limb.

Figure 35.

Figure 36.

X. THE WEIGHT

Shift of weight is indicated in the second space from the bottom of the page. Although physically speaking shift of weight is always present when the body is in movement, in the notation it is written only when it is visually predominant, or when it offers the most concise way of indicating an action, such as walking, jumping, etc.

Equal distribution of the weight of the body is indicated by the symbol · . When the weight is shifted, the projection of the longitudinal axis of the body on the horizontal plane coincides with one of the horizontal coordinates. This coordinate is identified as usual, by counting in the positive sense according to the scale in use. For instance, a shift of weight forward from zero position is written as 0 in the space reserved for shift of weight. (See Figure 37.)

In notating a series of steps in the same direction, the following convention is adopted: the steps are indicated by the compound symbol

↕
↕

abbreviated from the symbols used in writing in full the movements of flexion and extension in walking. Together with this, a number in the weight space shows the horizontal direction in which the weight is shifted throughout the movement sequence.

A number accompanied by the sign M (maximum) represents a shift of weight such as occurs in falling. (This falling



Figure 37.

movement is of course controlled in dance, by means of the action which follows it.)

The phenomenon of the jump, in which all contact with the ground is abandoned, is written in the weight space, using the symbol (=), derived from the symbol for absence of contact =. A jump in a given direction is shown by a number indicating the appropriate horizontal coordinate, e.g., $(\overset{2}{=})$.

XI. CONTACT

The sign for contact is ⊢ , with its derivatives. Contact for a part of the body with the ground is shown by the sign ⊢ in the appropriate space. Thus, in standing positions the sign appears in the spaces allotted to the feet.

Contact between parts of the body is shown by one of the other three forms ⊢ ⊥ ⊣ written in the spaces of both the limbs involved. A number shows which side of each limb is in contact. For example, contact between the palms of the hands would be written:

Left hand 2⊢
Right hand 6⊢

Contact of the extreme end of a limb (such as finger tips, or the "points" in Classical Ballet) is written $\dot{\vdash}$ or ⊣· . Release of contact is written = . When the foot is in contact with the ground, but does not bear weight, this is indicated by the sign ⊤ .

"Loose" contact, written L, is contact in which a limb or limbs are in contact with another surface, but move upon it. For instance, in rotation of the whole body with a foot as base, the sign L appears in the space for that foot. To indicate holding, the sign used is ⊦. Figure 38 illustrates some examples of contact with the ground.

XII. FRONT

In the lowest space on the manuscript page, four types of symbols may appear: numbers without brackets, numbers with brackets, the symbols for rotation (such as ⌒2, ⌒4, etc.), and the symbol for rotation about the lateral axis--"vertical rotation": ⊤.

In zero position the body is placed so that the horizontal direction 0 of the system of reference coincides with the direction forward from the body, and towards the observer. If, for purposes of analysis, it is required to reorientate the system of reference relative to this absolute zero position, the new front--the direction in which the 0 of the system faces--is indicated by a number without brackets.

From this point in the score, all movements would be written in relation to the new direction.

A number enclosed in brackets indicates the front of the body in relation to the 0 direction of the system of reference. Thus, with the system of reference orientated towards the observer, a position in which the body is in profile facing


Pelvis
R. Foot
L. Foot
Torso
R. Lower Leg
Foot
L. Lower Leg
Foot
L. Hand
R. Hand
L. Hand
R. Hand
L. Lower Leg
Foot
R. Lower Leg
Foot

Figure 38.

the observer's left, would be indicated by (2) in the "front" space.

When a rotation of the whole body occurs, this continuous change of front is written as a rotation in the "front" space, and the "loose contact" sign L is given to the part of the body which serves as base.

Rotatory movement is by definition movement about the longitudinal axis of the limb, but there are certain complex actions (such as forward and backward rolls, somersaults, etc.), in which the body as a whole rotates about its lateral axis. This is represented by the symbol ⊤ (positive) and ⊥ (negative), a composite derived from the signs of vertical plane movement and rotatory movement.

XIII. CONVENTIONS

13.1 Abbreviations.

(2↑) - a device serving as a "key" signature, given before the movement sequence. It indicates that all vertical plane movements with no bracketted number preceding the arrow are to be performed in the plane indicated here. In the example given, this is plane (2).

$f\binom{4}{0}$ - fixation may also precede a sequence, attached to a limb or limbs which are to remain in a constant relation to the system of reference despite movements of heavier limbs. For instance, the example shown, would indicate that by continuous adjustment the limb is maintained upright throughout the sequence.

13.2 Amounts of Movement.

When no amount is indicated, the magnitude of the movement is less than one unit.

m indicates the smallest amount possible.

M indicates the largest amount possible within the range of the joint involved.

- appended to a number signifies slightly less than the amount expressed by the number.

+ appended to a number signifies slightly more than the amount expressed by the number.

These last two are particularly useful in the notation of positions.

13.3 Parts of the Body - Special Cases.

The sign ↓ in the lower leg, appearing without indication of plane, expresses flexion of the lower leg towards the upper. The sign ↑ expresses extension. The principle underlying this convention is taken from the fact that from zero position, these would be the appropriate directions for the arrow in writing these movements in plane (0).

By application of the same principle to the foot, ↑ indicates flexion towards the lower leg; ↓ indicates extension.

The sign $\downarrow\atop\uparrow$ appearing on the line separating the upper and lower leg spaces, without indication of plane, indicates knee flexion. Similarly, the sign $\updownarrow$ indicates extension of

the knee. These signs are derived from the full notation of the same movements in zero position.

The symbol X indicates "contraction". The two extremities of the long axis of the torso--or of a part of the torso--approach one another in the same plane and with equal amounts of movement in opposite senses. The upper part moves in negative sense; the lower part in positive sense. The amount is written following the sign. For example, (2)XM indicates a contraction in plane (2), with maximal amount of movement, resulting in a concave curve to that side of the body. (The form of the symbol is based on the arrow-heads of plane movement signs, positive and negative.)

13.4 Auxilliary Signs.

When a movement or position in one plane involves the crossing of the legs or the arms, an asterisk * is written in the space of the limb which is to be in front of the other. The symbol ⌣ indicates that an over-all rounded shape is given to the position of several adjacent limbs (such as upper arm, forearm, hand) by slight flexion of all its joints. The symbol I indicates that several adjacent limbs are in a straight line. These two symbols are primitive alternatives for the sign X; in most cases it is preferable to use the latter.

Whenever necessary, the space allocated to each limb has been identified in the notation score, using the following abbreviations:

F	right	sh.	shoulder
L	left	hd.	head
fg.	fingers	n.	neck
1	thumb	tso.	torso
2	index	plv.	pelvis
3	middle	u.lg.	upper leg
4	ring	l.lg.	lower leg
5	little	ft.	foot
h.	hand	wt.	weight
f.a.	forearm	fr.	front
u.a.	upper arm		

PART B

MACHINE REPRESENTATIONS OF MOVEMENTS

(Michl and Melvin)

PRECEDING PAGE BLANK

MACHINE REPRESENTATIONS OF MOVEMENTS

The Eshkol-Wachmann (E-W) notation described is a position orientated notation in that the trajectory of the body can be computed exactly, and not a goal orientated notation as would be a notation which would specify that a certain event take place without indicating an exact manner of accomplishing it. As an example consider the differences between the order "starting with your arm vertically down make a vertical circle with your left hand, with your shoulders on the axis of the circle" and the order, "sit down on this chair". Absolute control over every movement is necessary for the first command to be obeyed, while in the second case, any manner of sitting down will be satisfactory as long as the goal is accomplished. Miss Eshkol is presently working on goal orientated features for the E-W notation, but as of now the only way to command a move to a prescribed position by E-W notation is to describe a string of commands which lead to it, and the only way to predict the results of a string of commands is by simulating movement on a model or by educated guessing.

For these reasons it seemed desirable to devise a simulator to study the potential of existing E-W commands. Use of human objects or mechanical models has several drawbacks, the most notable being the difficulty of recording observed data. Hand sketching projections of simple movements were

PRECEDING PAGE BLANK

made by Mr. Wachmann, and proved very satisfactory although too time consuming because of the computations involved. It was decided to write a computer program named DANCER which would speed the process up. Use of the computer provides accurate results, the possibility of processing large amounts of data in relatively little time, and direct graphical output through the use of a plotter attached to a main computer. An added advantage is insight gained into the logic of the notation by translating it into the purely abstract mathematical form of a computer program. Some of the knowledge acquired during the writing of DANCER was applied to the writing of a second computer program called STKMAN*, which uses different mathematical coordinates and provides the possibility of goal-like commands. Both computer programs will be described after brief disucssions on the physiology of movement and mathematical abstraction of the body.

I. PHYSIOLOGY OF MOVEMENT

Movement of the human body is, like all biological phenomena, the result of complex processes structured in such a manner as to allow maximum efficiency and integration of functions in view of a given goal. In watching a human body move an observer will only perceive the external

---

*Computer abbreviation of STICKMAN.

manifestations of movement and will, most of the time, remain totally unconcerned with the neural and muscular phenomena involved. Yet all movement does originate at the neural level and is only translated into visible phenomena after action by the muscles.

These simple facts suggest a hierarchical organization for the study of movement:

1) Volition of movement (neural level)
2) Execution of movement (muscular level)
3) Effect of movement (externally perceived movement)

The first level is that of the neurologist's or psychologist's. We will only retain a few observations made by neurologists concerning the functioning of the brain, mainly that nervous activity is in the form of electric-like waveforms and that the cerebellum acts as a filter and coordinator of movement commands. We will examine some of the consequences of this a bit later.

The second level is of somewhat more concern to us. The joints of the human body do not allow absolutely free movements--it is impossible, for instance, to throw one's leg backwards as far as forward, and the muscular arrangement of the body reflects these dispositions. Although we later offer a simplified model of the human body which gives all joints maximum freedom of movement we do so only while keeping in mind that a great many constraints do exist. Some ways

of adding constraints to the programs and notations are indicated in Section V.

Level 3 will be our most immediate area of concern: the configuration of the human body in space. We can define a movement notation as states of the human body combined with transitions between states. In the E-W notation, movements and positions of each limb are given by the locus of points traced by one end of the limb on its inscribed sphere. In the STKMAN system, positions and changes are given in terms of angles between connecting limbs. In both cases, the type of commands depends upon the mathematical system used to represent the body.

II. MATHEMATICAL ABSTRACTION OF THE HUMAN BODY

Since the human body is only capable of a finite number of positions, assuming that two positions must be discernible to the eye to quality as different, we will in fact be dealing with the study of the human body as a finite state automaton. We are unconcerned with the biological phenomena which permit the execution of transitions between states, but rather we wish to examine the external states adopted by the body during transitions. In using this approach, a first problem is how to sufficiently abstract the human body so that it may be represented as a reasonably simple system and be conveniently handled in mathematical terms.

A first observation is that most large bones are long and cylindrical, and can be approximated by a long, thin rods. Since the amount of soft tissues is approximately proportional to the size of the bones supporting them, parts of the body may be reasonably approximated by homogeneous rods. Notable exceptions such as the head, hands, feet,pelvis or torso can also be worked into this scheme by approximating them as thick cylinders and taking their main axis as rods, and furthermore in the case of the pelvis and torso, by adding additional points of contact with other parts on the surface of the cylinder itself making an assemblage of three rods (see Figure 1).



Figure 1. Approximations to torso and pelvis.

A very acceptable representation of the whole body is then an assemblage of stick like rods (see Figure 2). This representation is the basis of the STKMAN notation and is also used by the E-W notational scheme where limbs are often approximated by rods. We will henceforth call any of these rods "limbs".



Figure 2. Stick approximation to the body.

Study of such a system can be of a dynamic or kinematic nature. In the first case, the rods are assumed to have mass and all forces acting upon the system as well as muscular velocities must be known or computed to obtain the proper trajectories of the limbs. In a kinematic study the limbs are assumed to have no weight. Thus the only computations necessary are those which determine the position of the system.

Such a simplification is possible if we disallow harsh or jerky motions and hard contact of the system with immobile

objects, since important dynamic forces come into play in such circumstances. We are, in fact, specifying that only smooth and relatively slow movements be allowed.

That most movements of the body are in fact relatively smooth is due to the cerebellum and the dynamics of the body.

The nervous system smooths and coordinates neural commands by action of the cerebellum. Damage to this organ will result in incapacitating a patient by rendering smooth movements impossible and hindering coordination. An example of the amount of smoothing involved is provided in the articles by Denier van der Gon and Thuring (1965) and Denier van der Gon, et al. (1962) concerning the design of a handwriting simulator, where it is shown that even such an apparently staggered event as a signature can be simulated by a machine fed with a fairly uncomplicated and smooth signal. This indicates that smooth motions demand very smooth neural signals and that a great deal of neural coordination is built into any movement.

Assuming that commands for jerky motions are eliminated, command for a smooth movement may still result in jerky motion if the acceleration of the moving limbs is too large. A basic law of physics states that $a = \frac{F}{m}$ where a is acceleration, F force applied to the object and m the mass of the object. Since both F and m have a limited range of values for a given limb and its muscles, a will have a

limited range unless the limb is acted upon by outside forces, and moving additional attached limbs will decrease a even more. a will then be limited if the desired motion is not too harsh.

In the case of a large m, the influence of gravity becomes of some concern. Gravity's effect is minimized by the fact that the larger and hence heavier parts of the body are closer to the body's center of gravity than lighter parts. Light parts do not then usually move heavier ones. There are notable exceptions to this rule, such as in walking, and we may cover these exceptions by assuming that the body is not coming into contact with immobile objects. Walking, then, can simply be construed as being the raising and lowering of the feet by the body.

Given a kinematic system of connected sticks we have a basic structure with which to simulate movement of the body. Computer simulation of such a system will be based on storing sufficient information to completely define the system at given intervals of time. The E-W and STKMAN simulators store positions of limbs in a large array, each set of positions corresponding to the state of the system at a given time. This information can then be graphed to provide either these states at these timesteps or the trajectory of each limb, which can be printed or plotted accordingly. (See Figure 3.) The two methods are combined in DANCER to provide maximum information on the plots.



The State of the System at Specified Times.



Figure 3. The Space Curves of Two Limbs Executing the Same Movements as Above.

A system of n limbs will require at least 3(n+1) numbers to be defined. We need to know the position of one point of the system, and this point will act as a reference point for the system. Given this first point, we can construct a first limb originating from it by defining another point in space, or by defining the length and direction of the limb. In each case three numbers are needed since defining a direction in space requires two numbers. One can then define new limbs which originate from either point given once again a new triplet of numbers. (See Figure 4.) Accordingly the arrays used to store information in DANCER and STKMAN are both dimensioned 3 by (n+1) where n is the number of limbs in the system.

The main task of both programs consists of keeping track of the positions of the limbs and joints as commands are simulated.

III. THE E-W PROGRAM: DANCER

Two important aspects of the E-W notation are that the spheres in which limbs are inscribed are of fixed diameter and that the spheres have their south pole facing down vertically at all times. Given a fixed, or reference, point in the system, the position of other points can easily be computed given the E-W position of the limbs, their length and the unit angle used. Given 2 angles, a and b, and a length,l,

A LIMB CAN BE DEFINED USING:



Two Points A and B



One Point O, Two Angles α, β and a Length ℓ





Figure 4. Any additional limb attached to a given extremity of a single limb or node of a system, will require either an additional point, or two angles and a length to be defined.

which determine a limb centered in O, to determine E in rectangular coordinates, with u the unit angle in radians:

$$E_x = l \cos(bu-\tfrac{\pi}{2})\sin(-au) + Ox$$

$$E_y = l \cos(bu-\tfrac{\pi}{2})\cos(-au) + Oy$$

$$E_z = l \sin(bu-\tfrac{\pi}{2}) + Oz$$

(See Figure 5.) If another limb is added to OE, the same computation is repeated, replacing Ox, Oy, Oz by E_x, E_y, E_z, and a, b and l by their new values for the new limbs.



Figure 5. Representation of a limb.

Throughout these examples, we will hold the unit angle fixed at 45°, although full provision is made in the program for any divisor of 360°. We will call the origin of the system the fixed reference point and the origin of a limb the closest extremity to the absolute origin along the broken line consisting of interconnected limbs.

A limb's origin is a pivot point for the limb and is the center of the enclosing sphere. We number limbs in sequence, beginning with the limb attached to the absolute origin, and call a low numbered limb a heavier limb than a higher numbered one. We restrict ourselves to systems of interconnected limbs with no more than 2 limbs stemming from any function of limbs. This does not permit representation of the whole body, which is treated in STKMAN, but the system could have been expanded in order to do so. However, the main purpose of the E-W simulator is to study results of simultaneous E-W commands on interconnected limbs.

Commands used are input to the computer indicating, for each limb the beginning position, the type of movement, the total amount of movement in degrees and at what timestep this movement ends. Each limb may execute different movements sequentially. The types of movement allowed, with their coded number representations, are:

0 = no movement

1 = planar movement

2 = conical movement

3 = rotatory movement

4 = planar movement with rotation

5 = conical movement with rotation

As defined in E-W notation, to indicate the locus of the movement in case of planar or conical commands, an auxiliary point is to be given and treated in the following manner:

1) If the movement is a planar one, the auxiliary point is any point on the circle, other than the starting point or the other end of a diameter through the starting point. A center and two distinct points on the circumference fully define a circle (Figure 6).



Figure 6. Planar movement.

2) If the movement is a conical one, the auxiliary point is taken to determine the diameter of a circle intersecting the axis of the cone perpendicularly. Given the apex and this diameter, the cone is uniquely determined (Figure 7).



Figure 7. Conical movement.

Timesteps were determined by a rule of thumb which indicated that a rotation of 5° per timestep provided smooth curves when space curves were plotted. Since different limbs were given different velocities, it was decided to input this factor with the data instead of having it as a fixed or machine computed constant.

When reading in the data, the program creates a list of type and amount of movement for each limb at each timestep. The amount of movement is simply the total amount of the specific movement divided by the number of timesteps that type is to occur.

Actual computation of new positions is by use of a rotational matrix which rotates the moving limb, its intermediary point and all limbs lighter than the one in motion.

The computation depends on determination of the axis of rotation. For planar movement, this is the perpendicular to the plane of the circle at the center. For conical movement, it is the axis of the cone. The system is translated until the pivot point of the moving limb is at the origin. The whole system is then rotated about the z axis and x axis until the axis of rotation coincides with the Oz axis. The system is then rotated in the proper amount about the Oz axis and is rotated and translated back to its original position by reversing the previous steps. The matrix used for rotation is (Goldstein, 1950):

$$A=\begin{pmatrix} \cos\psi\cos\phi - \cos\theta\sin\phi\sin\psi & \cos\psi\sin\phi + \cos\theta\cos\phi\sin\psi & \sin\psi\sin\theta \\ -\sin\psi\cos\phi - \cos\theta\sin\phi\cos\psi & -\sin\psi\sin\phi + \cos\theta\cos\phi\cos\psi & \cos\psi\sin\theta \\ \sin\theta\sin\phi & -\sin\theta\cos\phi & \cos\theta \end{pmatrix}$$

The angles ϕ, ψ and θ are defined on Figure 8.

This matrix is the product of three matrices B, C and D defined in the following manner (Goldstein, 1950).

Rotation about Oz:

$$D=\begin{pmatrix} \cos\phi & \sin\phi & 0 \\ -\sin\phi & \cos\phi & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

Rotation about Ox:

$$C=\begin{pmatrix} 1 & 0 & 0 \\ 0 & \cos\theta & \sin\theta \\ 0 & -\sin\theta & \cos\theta \end{pmatrix}$$

Rotation about δ:

$$B=\begin{pmatrix} \cos\psi & \sin\psi & 0 \\ -\sin\psi & \cos\psi & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

(Using the notation of Figure 8.) Applying $D^{-1}C^{-1}$ then rotates the system back into its original position.

For any given timestep, if the system contains n limbs, limb 1 is moved first and with it the entire system, then limb 2 and the entire system less limb 1, etc., until limb n,



1) The Limbs are Translated Until Origin of Moving Limb is at Origin of Coordinate System.



2) The System is Rotated About OZ Until OX' is Perpendicular to δ. The Amount of Rotation is ϕ.



3) This System is Rotated About OX' Until OZ Coincides with δ. The Amount of Rotation is θ.

Any Rotation About OZ' Will Now be Equivalent to a Rotation About δ. This Rotation is ψ.

Figure 8. Rotation about a given axis.

the lightest limb, which carries no other limbs,is moved. The program then executes commands for the following time-step until all timesteps for all limbs have been exhausted.

Input is permissible in E-W coordinates or rectangular coordinates. In the event E-W coordinates are used, the unit angle has a default value of 45° unless otherwise specified, and a subroutine, named TRANSL, translates the input into rectangular coordinate values. Results come out as a printed table of positions for given times in rectangular and spherical coordinates. Note that spherical coordinate angles are not taken in the same direction as E-W coordinates: viewed from the top, the horizontal angle sweeps counter-clockwise, while in E-W it sweeps clockwise. Similarily, zero degrees is vertical down in E-W, vertically up in spherical for the vertical angle. Results are also obtained as plots of the space curves created by the joints of the limbs. Supplementary lines are drawn connecting points representing simultaneous times on different trajectories. The number of these is variable, and several features help enhance the plot. As an example of possible representations of the same movement, Figures 9 through 12c show results obtained from a typical 2 limb case. All plots are projections onto three imaginary perpendicular planes, two vertical and one horizontal. The two limbs are executing cones. The corresponding E-W command is



The first limb is executing a cone of 8 x 45 = 360°, the second limb a cone of 4 x 45 = 180°, starting from positions $\binom{1}{1}$ and $\binom{4}{4}$ respectively, and going through points $\binom{2}{3}$ and $\binom{?}{2}$.

In Figures 10a,b,c, the circular parts represent the trajectories of the limbs extremities. The numbers indicate the position of the limb such that every fifth timestep is indicated and the states of the limbs are indicated at every timestep. The numbers still refer to every fifth timestep and the axes have been deleted. The axes are not needed if one wants positions in terms of angles.

In Figures 12a,b,c, only the outermost trajectory is joined to the center point. This is to allow an easier identification of the trajectory's shape.

All figures are automatically scaled and the axes numbers adjusted accordingly, when the axes are used.

Printed output indicates the options used and movements specified on the title page. It then provides,for each limb, the position and direction of each limb of each timestep. The extremity of each limb is given by a triplet, the origin of the limb being either the system's origin in the

COORDINATES OF LIMB NUMBER 1

	X	Y	Z	HORI	VERT
0	-0.000	-0.707	0.707	-90	45
1	0.058	-0.693	0.728	-85	43
2	0.117	-0.659	0.743	-80	42
3	0.178	-0.634	0.753	-74	41
4	0.239	-0.608	0.757	-69	41
5	0.300	-0.583	0.755	-63	41
6	0.360	-0.558	0.748	-57	42
7	0.420	-0.533	0.734	-52	43
8	0.478	-0.509	0.716	-47	44
9	0.535	-0.485	0.691	-42	46
10	0.590	-0.463	0.662	-38	49
11	0.642	-0.441	0.627	-35	51
12	0.691	-0.421	0.588	-31	54
13	0.736	-0.402	0.544	-29	57
14	0.778	-0.385	0.496	-26	60
15	0.816	-0.369	0.444	-24	64
16	0.850	-0.355	0.389	-23	67
17	0.879	-0.343	0.331	-21	71
18	0.903	-0.333	0.271	-20	74
19	0.923	-0.325	0.208	-19	78
20	0.937	-0.319	0.144	-19	82
21	0.946	-0.315	0.078	-18	86
22	0.949	-0.314	0.012	-18	89
23	0.948	-0.315	-0.054	-18	93
24	0.941	-0.317	-0.119	-19	97
25	0.929	-0.322	-0.184	-19	101
26	0.911	-0.330	-0.247	-20	104
27	0.889	-0.339	-0.309	-21	108
28	0.861	-0.350	-0.368	-22	112
29	0.829	-0.364	-0.424	-24	115
30	0.793	-0.379	-0.477	-26	118
31	0.753	-0.395	-0.526	-28	122
32	0.708	-0.414	-0.572	-30	125
33	0.661	-0.433	-0.613	-33	128
34	0.610	-0.455	-0.649	-37	130
35	0.556	-0.477	-0.681	-41	133
36	0.500	-0.500	-0.707	-45	135
37	0.442	-0.524	-0.728	-50	137
38	0.383	-0.549	-0.743	-55	138
39	0.322	-0.574	-0.753	-61	139
40	0.261	-0.595	-0.757	-66	139
41	0.200	-0.624	-0.755	-72	139
42	0.140	-0.649	-0.748	-78	138
43	0.080	-0.674	-0.734	-83	137
44	0.022	-0.698	-0.716	-88	136
45	-0.035	-0.722	-0.691	-93	134
46	-0.090	-0.744	-0.662	-97	131
47	-0.142	-0.766	-0.627	-100	129

Figure 9. Computer printed output giving positions in rectangular coordinates and spherical angles for each timestep.

48	-0.191	-0.788	-0.588	-104	126
49	-0.236	-0.805	-0.544	-106	123
50	-0.278	-0.822	-0.496	-109	120
51	-0.316	-0.838	-0.444	-111	116
52	-0.350	-0.852	-0.389	-112	113
53	-0.379	-0.864	-0.331	-114	109
54	-0.403	-0.874	-0.271	-115	106
55	-0.423	-0.882	-0.208	-116	102
56	-0.437	-0.888	-0.144	-116	98
57	-0.446	-0.892	-0.078	-117	94
58	-0.449	-0.893	-0.012	-117	91
59	-0.448	-0.893	0.054	-117	87
60	-0.441	-0.890	0.119	-116	83
61	-0.429	-0.885	0.184	-116	79
62	-0.411	-0.877	0.247	-115	76
63	-0.389	-0.868	0.309	-114	72
64	-0.361	-0.857	0.368	-113	68
65	-0.329	-0.844	0.424	-111	65
66	-0.293	-0.829	0.477	-109	62
67	-0.253	-0.812	0.526	-107	58
68	-0.208	-0.793	0.572	-105	55
69	-0.161	-0.774	0.613	-102	52
70	-0.110	-0.753	0.649	-98	50
71	-0.056	-0.730	0.681	-94	47

COORDINATES OF LIMB NUMBER 2

	X	Y	Z	HORI	VERT
0	-0.000	-0.707	1.707	0	0
1	0.169	-0.650	1.721	16	7
2	0.338	-0.594	1.717	16	13
3	0.505	-0.540	1.693	16	20
4	0.669	-0.489	1.652	16	27
5	0.827	-0.440	1.593	15	33
6	0.977	-0.395	1.518	15	40
7	1.119	-0.355	1.427	14	46
8	1.250	-0.320	1.322	14	53
9	1.370	-0.290	1.205	13	59
10	1.478	-0.266	1.077	13	65
11	1.572	-0.248	0.939	12	72
12	1.652	-0.236	0.794	11	78
13	1.717	-0.232	0.643	10	84
14	1.767	-0.234	0.488	9	90
15	1.802	-0.242	0.331	7	97
16	1.821	-0.258	0.173	6	102
17	1.826	-0.280	0.017	4	108

18	1.817	-0.308	-0.135	2	114
19	1.794	-0.342	-0.283	-1	119
20	1.757	-0.382	-0.424	-4	125
21	1.709	-0.427	-0.558	-8	130
22	1.649	-0.477	-0.683	-13	134
23	1.580	-0.531	-0.798	-19	138
24	1.502	-0.589	-0.901	-26	141
25	1.416	-0.649	-0.993	-34	144
26	1.324	-0.713	-1.073	-43	146
27	1.228	-0.778	-1.141	-52	146
28	1.128	-0.844	-1.195	-62	146
29	1.026	-0.911	-1.237	-70	144
30	0.924	-0.978	-1.267	-78	142
31	0.821	-1.045	-1.284	-84	139
32	0.721	-1.110	-1.289	-89	136
33	0.623	-1.174	-1.284	-93	132
34	0.528	-1.237	-1.267	-96	128
35	0.438	-1.296	-1.242	-98	124
36	0.354	-1.354	-1.207	-100	120
37	0.275	-1.408	-1.165	-101	116
38	0.202	-1.459	-1.116	-101	112
39	0.136	-1.506	-1.061	-101	108
40	0.077	-1.551	-1.002	-101	104
41	0.025	-1.591	-0.939	-100	101
42	-0.021	-1.628	-0.874	-99	97
43	-0.060	-1.662	-0.806	-98	94
44	-0.092	-1.691	-0.738	-97	91
45	-0.118	-1.718	-0.670	-95	89
46	-0.139	-1.741	-0.602	-93	87
47	-0.154	-1.762	-0.536	-91	85
48	-0.165	-1.779	-0.471	-88	83
49	-0.171	-1.794	-0.409	-86	82
50	-0.174	-1.806	-0.349	-84	82
51	-0.175	-1.816	-0.292	-82	81
52	-0.173	-1.824	-0.237	-80	81
53	-0.169	-1.831	-0.185	-78	82
54	-0.164	-1.836	-0.135	-76	82
55	-0.158	-1.839	-0.088	-75	83
56	-0.151	-1.841	-0.043	-73	84
57	-0.145	-1.842	0.001	-72	85
58	-0.138	-1.842	0.044	-72	87
59	-0.132	-1.841	0.085	-72	88
60	-0.127	-1.839	0.126	-72	90
61	-0.121	-1.836	0.168	-72	91
62	-0.116	-1.832	0.209	-73	92
63	-0.111	-1.827	0.252	-74	93
64	-0.106	-1.821	0.296	-75	94
65	-0.099	-1.813	0.341	-77	95
66	-0.092	-1.804	0.388	-78	95
67	-0.084	-1.793	0.437	-80	95
68	-0.073	-1.781	0.488	-82	95
69	-0.060	-1.766	0.541	-84	94
70	-0.044	-1.749	0.595	-86	93
71	-0.024	-1.729	0.650	-88	92



Figure 10a. Normal line density with axis (X-Y projection).



Figure 10b. Normal line density with axis (X-Z projection).



Figure 10c. Normal line density with axis (Y-Z projection).



Figure 11a. Maximum line density (X-Y projection).



Figure 11b. Maximum line density (X-Z projection).



Figure 11c. Maximum line density (Y-Z projection).



Figure 12a. Maximum line density and outermost trajectories joined to center (X-Y projection).



Figure 12b. Maximum line density and outermost trajectories joined to center (X-Z projection).



Figure 12c. Maximum line density and outermost trajectories joined to center (Y-Z projection).

case of the first limb, or the extremity of the previous limb in the case of other limbs. The direction is given in spherical coordinates, as indicated earlier. A flowchart and listing of DANCER are included in the appendix.

A routine checking for intersection of limbs was included in an earlier version of DANCER. This feature was found to be of little value and very time consuming and was consequently removed in later versions.

IV. A MODEL OF THE HUMAN BODY: STKMAN

The first step in constructing a model of the human body is to decide on how the body is to be described. It was decided to use a system of rigid limbs as in the E-W notation (see Figure 2). When constructing a coordinate system to describe such a model,with so many parts, it is essential to adopt a mathematical notation which is both flexible and easily manipulated. The first problem in such a construction is to adopt an ordering of the limbs which was done as in Figure 13. The body is considered as being made up of five limb sequences of four limbs each. The pelvis and lower back are considered as being made up of three limbs to preserve symmetry. Next a right-handed rectangular coordinate system is considered to be rigidly embedded in each limb with the z-axis along the long axis of the limb (see Figure 13). As drawn in Figure 13, the (private) coordinate systems are embedded in the limbs so



Figure 13. Private imbedded coordinate system.

that the coordinate axes are as in the zero position of the E-W notation. Since each limb is considered as a mathematically rigid body and are connected as in Figure 2, a mathematical description of the configuration of the body consists of three parts:

1) the position of one point in the body,

2) the length of each limb, and

3) the orientation of each limb.

It was decided to use the position of the pelvis, the first limb in the first sequence, as fundamental, i.e., its position in an external coordinate system is assumed to be given. The lengths of the limbs are contained in the 5 x 4 array $L_{m,n}$ (m=1,...,5, n=1,...,4) where $L_{m,n}$ is the length of the nth limb in the mth sequence of limbs.

The description of the orientation of a rigid body requires three angles. Of course, the angles may be referred to any rectangular coordinate system. The E-W notation usually uses an external coordinate system. However such a coordinate system has the disadvantage that whenever a heavy limb is moved and all of the lighter limbs do not change their relative orientation, all of the angles describing the lighter limbs change. For this reason, in STKMAN a system of angles was adopted which gives the orientation of the nth limb in terms of the coordinate system attached to the (n-1)st limb. The angles describing the limb are the standard Eulerian angles (θ,ϕ,ψ) described in Goldstein's Classical

Mechanics (1950) (see Figure 14). Thus the orientation of all the limbs is given by the set of sixty angles ($\theta_{m,n}$, $\phi_{m,n}$, $\psi_{m,n}$) which is referred to as the configuration space. The angle between the z-axis of the nth limb and that of the (n-1)st limb in the mth sequence is $\theta_{m,n}$. The measurement of the other two angles requires the use of the line of nodes which is the intersection of the ($x_{m,n-1}$, $y_{m,n-1}$) plane with the ($x_{m,n}$, $y_{m,n}$) plane. $\phi_{m,n}$ is the angle between the $x_{m,n-1}$ axis and the line of nodes in the ($x_{m,n-1}$, $y_{m,n-1}$) plane, and $\psi_{m,n}$ is the angle between the line of nodes and the $x_{m,n}$ axis in the ($x_{m,n}$, $y_{m,n}$) plane. Varying $\theta_{m,n}$ rotates the nth limb about the line of nodes; varying $\phi_{m,n}$ rotates the z axis of the nth limb about the z axis of the (n-1)st limb; and varying $\psi_{m,n}$ rotates the nth limb about its own z axis. The orientation of the axes of the nth limb with



Figure 14. Eulerian angles.

respect to the axis of the (n-1)st limb is given by the columns of the matrix

$$\begin{pmatrix} \cos\psi\cos\phi - \cos\theta\sin\phi\sin\psi & -\sin\psi\cos\phi - \cos\theta\sin\phi\cos\psi & \sin\theta\sin\phi \\ \cos\psi\sin\phi + \cos\theta\cos\phi\sin\psi & -\sin\psi\sin\phi + \cos\theta\cos\phi\cos\psi & -\sin\theta\cos\phi \\ \sin\theta\sin\psi & \sin\theta\cos\psi & \cos\theta \end{pmatrix}$$

The first column gives the orientation of the $x_{m,n}$ axis with respect to the (m,n-1) system, the second column that of the $y_{m,n}$ axis and the third is for the $z_{m,n}$ axis. Let $a^{m,n}_{i,j}$ denote this orientation matrix, the first superscript denotes the limb sequence, m=1,...,5, the second superscript the limb number, n=1,...,4, the first subscript refers to the rows of the above matrix, i=1,2,3, and the second subscript the column, j=1,2,3. Thus the orientation of the $z_{m,n}$ axis relative to the (m,n-1) system is given by the three numbers $a^{m,n}_{i,j}$.

In terms of these relative angles, the zero position of the E-W notation is given by Figure 15. The circled angles are constrained to be as given to correspond to the two degrees of freedom in some joints. In addition since the pelvis is rigid, the following constraints are also imposed:

$$\theta_{2,1} = 90° + \theta_{1,1}, \quad \phi_{2,1} = \phi_{1,1}, \quad \psi_{2,1} = \psi_{1,1}$$

$$\theta_{3,1} = 90° + \theta_{1,1}, \quad \phi_{3,1} = 180° + \phi_{1,1}, \quad \psi_{3,1} = 180° + \psi_{1,1}.$$

The description of the model becomes complete when it is stated how any position of the body can be computed given

Limb sequence	Limb	θ	φ	ψ
1	1	0	0	0
	2	0	0	0
	3	0	0	0
	4	0	0	0
2	1	90°	0	0
	2	90°	0	0
	3	0	270°	90°
	4	90°	90°	0
3	1	90°	180°	180°
	2	90°	180°	180°
	3	0	270°	90°
	4	90°	90°	0
4	1	90°	0	0
	2	90°	0	0
	3	0	90°	270°
	4	0	0	0
5	1	90°	180°	180°
	2	90°	180°	180°
	3	0	90°	270°
	4	0	0	0

Figure 15. Zero position.

the position of the pelvis $(X, Y, Z) = X_i$, the lengths of the limbs $L_{m,n}$ and the configuration space $(\theta_{m,n}, \phi_{m,n}, \psi_{m,n})$ which is now done. This is simply a matter of vector addition. From the following example, the reader should see how the process is carried out in general: suppose the position of the tip of the left hand is to be computed. The position of the pelvis is X_i, the orientation of the pelvis is given by the matrix $a^{1,1}_{i,j}$ so the position of the top of the pelvis is

$$x^2_i = L_{1,1} a^{1,1}_{i,3} .$$

The orientation of the chest relative to the pelvis is $a^{1,2}_{i,j}$, so the orientation of the chest relative to the external coordinate system is given by the matrix product $A^{1,2}_{i,j}$ where

$$A^{1,2}_{i,j} = a^{1,1}_{i,n} \, a^{1,2}_{n,j}$$

and the summation convention is used. Thus, the position of the top of the chest is

$$X^2_i = X^1_i + L_{1,2} A^{1,2}_{i,3} .$$

Continuing in this manner the position of the left finger tips is, (c.f., Figure 2),

$$X_i = L_{1,1} a^{1,1}_{i,3} + L_{1,2} A^{1,2}_{i,3} + L_{4,1} A^{4,1}_{i,3} + L_{4,2} A^{4,2}_{i,3} + L_{4,3} A^{4,3}_{i,3} + L_{4,4} A^{4,4}_{i,3} .$$

where the orientation matrices relative to the exterior coordinate system are found as

$$A^{4,1}_{i,j} = A^{1,2}_{i,k} a^{4,1}_{k,j}; \quad A^{4,2}_{i,j} = A^{4,1}_{i,n} a^{4,2}_{n,j}; \quad \text{etc.}$$

Thus, a computation algorithm for finding the position of any point in the body is obtained. A subroutine was written to compute and plot the limbs of the body given the position of the pelvis, the length of the limbs and the configuration space. The program was then tested for various positions (see plots, pp. 163-167).

With the completion of this subroutine called PØSIT (for position), it becomes possible to compute the motions of the body by giving the position of the pelvis and the configuration space as functions of time. This was done for two relatively simple motions, 1) bending over and swinging arms, and 2) walking. Finding the angles as functions of time for (1) was relatively simple and is not described here. The second motion was more difficult and is described in detail here.

The essential property of a person walking is propelling the body along at a constant velocity. For STKMAN this amounts to giving the pelvis a constant velocity and then moving the legs in such a manner that it appears the legs are causing movement. The minimum number of angles are used (see Figure 16),and no rotation of the legs is allowed, only bending, and the foot is held parallel to the floor. The reader may verify that if bending at the hip, knee and ankle in the forward direction are the only motions used, then the



Figure 16. Abstraction of a bending leg.

only angles varied from zero position are those indicated in Figure 15. From the figure it follows that

$$z_r = l_2\cos\phi_{22} + l_3\cos(\theta_{23} - \phi_{22}),$$

$$x_r = l_2\sin\phi_{22} - l_3\sin(\theta_{23} - \phi_{22}),$$

$$z_r = l_2\cos(180°-\phi_{32})+l_3\cos[\theta_{33}-(180°-\phi_{32})],$$

$$x_r = l_2\sin(180°-\phi_{32})-l_3\sin[\theta_{33}-(180°-\phi_{32})].$$

The condition that the feet remain parallel to the floor is

$$\theta_{24} = 90° + \theta_{23} - \phi_{22},$$

$$\theta_{34} = \phi_{32} + \theta_{33} - 90°.$$

A walking routine is obtained by giving $z_r(*)$, $x_r(*)$, $z_r(t)$ and $x_r(t)$ as the appropriate functions of time. The angles

as functions of time are found by solving the above equations, for example,

$$\cos\theta_{23} = \frac{x_r^2 + z_r^2 - (l_2^2+l_3^2)}{2l_2l_3}$$

$$\tan\phi_{22} = \frac{x_r(l_2+l_3\cos\theta_{23}) + z_r l_3\sin\theta_{23}}{z_r(l_2+l_3\cos\theta_{23}) - x_r l_3\sin\theta_{23}} .$$

A program was written to compute and plot the position of STKMAN for various assumptions about the time variations of x_r, z_r, x_n, z_n. (See listing and plots.)

It was also attempted to write a program to translate the E-W notation into the relative angles of STKMAN , but it was found that this was not possible without further consultation for two reasons. First, the E-W notation refers the orientation of limbs to an exterior coordinate system only when the limb is moving, otherwise the previous orientation is maintained. This causes no difficulty for a person reading the notation, but it proves to be rather difficult to program. The second problem was the way that the notation of a limb about its own axis is treated in the E-W notation. As we understand , the rotational state of a limb is given by the azimuth of the projection of the normal (the x-axis of the limb) to the limb upon the (x,y)-plane. For certain orientations this specification is simply not unique. For example, if z axis of the limb is oriented along the x axis, then the E-W notation cannot specify the direction of the

normal to the limb which may lie anywhere in the (x,z) plane. This difficulty may be overcome by specifying the normal by two polar angles, or by one Eulerian rotation angle.

Further work on STKMAN is possible. In particular it would be interesting to use this model to obtain plots of more complex motions, such as various dances. This of course would require much more work to obtain the angles as functions of time. It would also be interesting to do the inverse problem of given a particular motion of the body (i.e., the position of various limbs of the body as functions of time) find the corresponding angles. The problem of the dynamical motion of the body remains to be done. The equations of motion must be obtained by the rather difficult problem of referring the gyroscopic equations of motion to an arbitrary moving coordinate system.

V. CONCLUSION

Although both DANCER and STKMAN are basically position oriented notational programs, it is possible to input subroutines to STKMAN which in fact control movement as in the WALK subroutine. It is a simple matter to make STKMAN accept goal type commands of the sort "walk to such or such a place" by computing internally in the program the length of the steps to take, the direction to be taken, etc. It would be terribly cumbersome, however, to program each possible type of human movement in this manner. The program would soon

reach an extremely large size without any guarantee of exhausting possible movements. Optimization is here a key problem, and seems to be a logical next area of investigation.

Other problems remain. Limbs of a simulator behaving like human limbs would be subject to dynamic constraints, which, as pointed out earlier, lead to difficult equations of motion. Forbidden regions of movement caused by joint structure could be determined by a table hookup system in STKMAN (see Prost, 1967 and Figure 17), but these interdictions would not be reflected in the notation. A more refined notation could solve both the dynamic and range problems, by specifying syntactic rules forbidding impossible movements and taking into account the physical characteristics of the limbs being moved.

The problem of defining such a complete notation reduces most easily to that of determining proper input to a finite state or context sensitive automaton which would simulate movements of the body. Although STKMAN is such an automaton, it is hardly discriminating enough in the input it accepts: it could, however, be adapted to accept more rigorous input. As an example, the WALK subroutine can be approximated by the automaton of Figure 18. This automaton will accept the alphabet

S = start

L = left leg moves forward

R = right leg moves forward

E = movement stops



Figure 17. Ranges of allowable movement in shoulder and elbow.



Figure 18. Simple automaton accepting walking commands.

It is easily verified that the string SLRLRE is acceptable while the string SLLE is not. The grammar generated is then

1. $S \rightarrow RS_R \mid LS_L$
2. $S_R \rightarrow LS \mid E$
3. $S_L \rightarrow RS \mid E$

(1. Starting can only lead to moving the right or left leg.
2. After the right leg has been moved, one can only move the left leg or stop.
3. After the left leg has been moved, one can only move the right leg or stop.)

Such grammars could possibly be extended to include more complex sequences of movements and seem most promising for establishing a complete movement notation based on the E-W notation.

REFERENCES

1. Denier van der Gon, J. J. and J. Ph. Thuring, "The Guiding of Human Writing Movements," Kybernetik, 2 (4), 145-148 (1965).

2. Denier van der Gon, J. J., J. Ph. Thuring and J. Strackee, "A Handwriting Simulator," Physics in Medicine and Biology, 6 (3), 407-414 (1962).

3. Goldstein, H., Classical Mechanics, Addison-Wesley Publishing Company, Inc., Reading, Massachusetts, 399 pp. (1950).

4. Prost, J. H., "Bipedalism of Man and Gibbon Compared Using Estimates of Joint Motion," American Journal of Physical Anthropology, 26 (2), 135-148 (1967).

APPENDICES

APPENDIX Ia. FLOWCHART OF DANCER

page 1


BEGIN
RESERVE STORAGE BY DIMENSIONING ARRAYS.
IS THERE INPUT DATA?
NO
STOP-END OF COMPUTATION.
YES
READ AND PROCESS INPUT. INITIALIZE ARRAYS USED IN CONTROLLING TRANSFERS WITHIN THE PROGRAM.
IS INPUT GIVEN IN E-W NOTATION?
YES
TRANSLATE INTO CARTESIAN COORDINATES.
NO
PRINT TITLE PAGE CONTAINING INFORMATION AS TO THE VALUES AND TYPE OF INPUT USED
COMPUTE AND STORE THE LENGTH OF ALL LIMBS IN THE SYSTEM.
A

page 2


page 1
A
INITIALIZE COUNTERS CONTAINING THE NUMBER OF THE LIMB BEING MOVED AND THE CURRENT TIMESTEP
page 3
D
UPDATE COUNTERS.
HAVE ALLTHE REQUIRED MOVEMENTS FOR THIS SET OF DATA BEEN COMPUTED?
YES
P
page 4
NO
LOOK UP TYPE AND AMOUNT OF MOVEMENT REQUIRED FOR THIS LIMB AT THIS TIME STEP
DOES MOVEMENT=0?
YES
NO
IS THIS THE BEGINNING OF A CONICAL MOVEMENT?
YES
SET UP COEFFICIENTS TO SIMULATE PLANAR MOVEMENT.
NO
B
page 3
C
page 3


page 2
B
IS MOVEMENT A PURE ROTATION?
YES
NO
page 2
C
COMPUTE SPECIAL COEFFICIENTS OF AXIS OF MOVEMENT.
PLANAR CASE; COMPUTE COEFFICIENTS OF AXIS OF MOVEMENT AND ROTATE LIMB IN MOVEMENT.
ROTATE SYSTEM DEPENDENT OF LIMB STORE NEW VALUES.
DID ANY TWO LIMBS INTERSECT?
YES
PRINT ERROR MESSAGE AND QUIT FOR THIS DATA SET.
E
page 1
NO
STORE NEW VALUES IN ARRAYS USED IN PLOTTING. TRANSLATE NEW POSITIONS INT B-W NOTATION AND STORE FOR LATER PRINTING.
D
page 2


P
page 2
SCALING OF PLOTTING ARRAYS AND INITIALI-ZATION OF CONSTANTS USED IN PLOTTING.
PRINT COMPUTED DATA.
DETERMINE PROJECTION TO BE PLOTTED.
PLOT.
HAVE ALL PROJEC-TIONS BEEN PLOT-TED?
NO
YES
E
page 1

APPENDIX Ib. PROGRAM LISTING OF DANCER

```
C0C1                IMPLICIT REAL*8(A-H,O-Z)
C002                     REAL*4     CR1,CR2,CR3,TS,TX,TY,TZ,XLIN,XLJN ,YLIN,YLJN
C003               REAL*4 XPL1,YPL1,ZPL1,FR,XTRACE,YTRACE,ZTRACE,TSA
C004                REAL*4 SIGX,SIGY,SIGZ,TM,ALX,ALY
0005                DIMENSION KSPCOU(10),KCENTR  (10,10,2)
0006                DIMENSION PLOT(5,150,3),XPL1(152),YPL1(152),ZPL1(152),ALONG(11)
                   1 ,XTRACE(11),YTRACE(11),ZTRACE(11),FR(3)
0007                DIMENSION IPECS(11,152,2)
C0C8                DIMENSION KNGAR(11,10)
0009                DIMENSION  ROTR(10,200)
C01C                DIMENSION TX(2),TY(2),TZ(2),TS(2),TSA(2)
0011                DIMENSION ARRAY(11,6),TSTEP(11),AMOV(11),KTYP(11)
0012                DIMENSION XLIN(2),YLIN(2),XLJN(2),YLJN(2)
0013                DIMENSION CR1(3),CR2(3),CR3(3)
C014                DIMENSION AINTER(10,20,3), LCOUNT(10)
0015                DIMENSION ANGLE(10,200),ITYPE(10,200)
0016                DIMENSION           AD(11),CLONG(11) ,ISTEP(11)
0017                DIMENSION TEMM(2,11,3)
0018               DIMENSION SIGX(500),SIGY(500),SIGZ(500)
0019                DIMENSION ALX(5),ALY(5)
0020               DIMENSION TM(2)
0021          2     FORMAT(3F10.5,I10)
C022          3    FORMAT(5I5)
0023          4     FORMAT(3I5,3F10.5)
0024          5     FORMAT(3F10.5)
0025          6    FORMAT(I5)
C026          8    FORMAT(45X,24H THE UNIT ANGLE EQUALS     ,I5)
0027         11     FORMAT(45X,34H E-W NOTATION WAS USED FOR INPUT  )
0028         12    FORMAT(45X,51H RECTANGULAR COORDINATE VALUES WERE USED FOR INPUT
                  I  )
0029         13     FORMAT(45X,21H THIS SYSTEM CONTAINS ,I3,6H LIMBS ///////)
0030         14    FORMAT(///96X,6H UP TO,/18X,13H LIMB JOINTS ,32X,20H INTERMEDIARY
                  1 POINTS,12X,1CH ITERATION,1X,6H TYPE  ,4H MOV )
0031         15   FORMAT(45X, 7F EVERY  ,I3,26H POINTS WILL BE CONNECTED  )
0032          16   FORMAT(1H1,////,50X,24H ********************** /,52X,21H *TABLE
                  1OF RESULTS * //////)
0033         17   FORMAT(45X,5CH ONLY THE LIGHTEST LIMB WILL BE JOINED TO CENTER   )
```

```
0034          870   FORMAT(3E32.16)
0035          871   FORMAT(//18H UNITY IS EQUAL TO  ,F10.5)
0036          874   FORMAT(9X,2H X,8X,2H Y,8X,2H Z,6X,5H HORI,6H  VERT  )
0037          875   FORMAT (I4,3F10.3,3X,2I6 )
0038           876  FORMAT(1H1,30H COORDINATES OF LIMB NUMBER     , I4/)
0039          882   FORMAT(10H TROUVLE   )
0040          884   FORMAT(10H TROUBLE   )
0041          886   FORMAT(1H1,32H WRONG TYPE OF MOVEMENT FOR LIMB   ,I5)
0042          888   FORMAT (48X,3F16.4,I7,I6,I5)
0043         892    FORMAT(3F16.4)
0044          893   FORMAT(2I15,2X,F16.4)
0045          894   FORMAT(48X,2I15,2X,F16.4,I7,I6,I5)
0046          896   FORMAT(50X,3F10.4)
0047          897   FORMAT(60X,3F10.4)
0048          899   FORMAT(1H1,39H NO INTERMEDIARY POINT GIVEN FOR LIMB      ,I3)
              CCCCC CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
              C
              C
0049                PI = 3.14159265358979 3
0050           19   KT=0
0051                KSW=0
0052                KTYPC=9
0053                KC=1
0054                KWCR = 1
0055                  KSIG=0
0056               CC 729 KC=1,10
0057               CC 729 KR=1,200
0058               ITYPE(KQ,KR)=C.0
0059           729  CONTINUE
              C
              C
```

```
C
C       CONTROL SECTION FOR READING IN OF INPUT

0060      705   READ(5,3) NOT,KVIEW,KANGLE,LSPACE,KAXIS
0061            IF(KVIEW.EQ.99) GO TO 4500
0062      707   READ(5,2) (ARRAY(KC,LLL),LLL=1,3),LCHECK
0063            IF(LCHECK.EQ.99) GO TO 22
0064            ICOUNT=1
0065            KOLD=1
0066      708   READ(5,4) KSTEP,LTYPE,MOTOT,(AINTER(KC,ICOUNT,LLL),LLL=1,3)
0067            IF(KSTEP.EQ.0) GO TO 709
0068            IF(LTYPE.GT.5) GO TO 4503
0069            KROTA=0
0070           IF(LTYPE.NE.4.AND.LTYPE.NE.5) GO TO 706
0071           READ(5,6)KROTA
0072      706  CONTINUE
0073            KCONTR  (KC,ICOUNT,1)=KSTEP
0074            KCONTR  (KC,ICOUNT,2)=LTYPE
0075            KNGAR(KC,ICOUNT)=MOTOT
0076            ICOUNT=ICOUNT+1
0077            TEMP1=MOTOT
0078            TEMP1=TEMP1/KSTEP
0079            TEMP1=TEMP1*(PI/180.)
0080            TEMP2=KROTA
0081            TEMP2=(TEMP2/KSTEP)*(PI/180.)
0082            DO 701 K=KOLD,KSTEP
0083            ITYPE(KC,K)=LTYPE
0084            ROTR(KC,K)=TEMP2
0085      701   ANGLE(KC,K)=TEMP1
0086            KOLD=KSTEP+1
0087            GO TO 708
0088      709   ISTEP(KC)=KOLD-1
0089            IF(ICOUNT.EQ.1) GO TO 4502
0090            KSPCOU(KC)=ICOUNT-1
0091            LCOUNT(KC)=2
0092            ARRAY(KC,4) = AINTER(KC,1,1 )
0093            ARRAY(KC,5) = AINTER(KC,1,2 )
0094            ARRAY(KC,6) = AINTER(KC,1,3 )
```

```
0095                KC=KC+1
0096                GO TO 707
                C
                C   AND INITIALIZATION OF ARRAYS USED IN PLOTTING THE ORIGIN OF SYSTEM
                C
0097          22    NN=KC-1
0098                DO 800 MM=1,102
0099                XPL1(MM) = 0.
0100                YPL1(MM) = 0.
0101                ZPL1(MM) = 0.
0102          800   CONTINUE
0103                CR1(1) = ARRAY(1,1)
0104                CR2(1) = ARRAY(1,2)
0105                CR3(1) = ARRAY(1,3)
                C
                C
                C
                C     PRINTING OF TITLES
                C
0106                 WRITE(6,16)
0107                WRITE(6,13) NN
0108                IF(LSPACE.EQ.0) LSPACE=5
0109                WRITE(6,15) LSPACE
0110                IF(LSPACE.GE.0) GO TO 536
0111                WRITE(6,17)
0112          536   CONTINUE
                C
                C
                C
                C     COORDINATE TRANSLATION FOR E/W NOTATION
                C      AND PRINTING OF VALUES AT BEGINNING OF COMPUTATION
                C
0113                 IF(NCT.NE.1) GO TO 25
0114                WRITE(6,11)
0115                WRITE(6,8) KANGLE
0116                DO 543 KKL=1,NN
0117          543   CONTINUE
0118                WRITE(6,14)
0119                WRITE(6,892) CR1(1),CR2(1),CR3(1)
0120                DO 544 KK=1,NN
0121                KTEMP=KSPOCU(KK)
0122                DO 545 KL=1,KTEMP
0123                KFOO=AINTER(KK,KL,1)+0.1
0124                LFOO=AINTER(KK,KL,2)+0.1
0125                R =  AINTER(KK,KL,3)
```

```
0126                WRITE(6,894) KFOO,LFOO,R,(KCONTR  (KK,KL,KU),KU=1,2),KNGAR(KK,KL)
0127                    CALL TRANSL(KFCC,LFOC,R,KANGLE,X,Y,Z,KTEST)
0128                IF(KTEST.EC.1) GO TO 19
0129                AINTER(KK,KL,1)=X +ARRAY(KK,1)
0130                AINTER(KK,KL,2)=Y  +ARRAY(KK,2)
0131                AINTER(KK,KL,3)=Z +ARRAY(KK,3)
0132          545   CONTINUE
0133                KFCC=ARRAY(KK+1,1)+0.1
0134                LFOO=ARRAY(KK+1,2)+0.1
0135                R =  ARRAY(KK+1,3)
0136                WRITE(6,893) KFOO,LFOO,R
0137                    CALL TRANSL(KFCC,LFOC,R,KANGLE,X,Y,Z,KTEST)
0138                IF(KTEST.EC.1) GO TO 19
0139                ARRAY(KK+1,1)=X +ARRAY(KK,1)
0140                ARRAY(KK+1,2)=Y +ARRAY(KK,2)
0141                ARRAY(KK+1,3)=Z  +ARRAY(KK,3)
0142               ARRAY(KK,4)= AINTER(KK,1,1)
0143               ARRAY(KK,5)= AINTER(KK,1,2)
0144               ARRAY(KK,6)= AINTER(KK,1,3)
0145          544   CONTINUE
0146                GO TO 28
            CCCCC CCCC
```

```
C
C      COMPUTATION OF THE POSITION OF THE FIRST POINT IN SPHERICAL
C      COORDINATES AND STORING OF THE INFORMATION IN THE ARRAY ''IPECS''
C      USED FOR OUTPUT PRINTING
0158            DO 588 KSP=1,NN
0159            PLOT(KSP,1,1) = ARRAY(KSP+1,1)
0160            PLOT(KSP,1,2) = ARRAY(KSP+1,2)
0161     588    PLOT(KSP,1,3) = ARRAY(KSP+1,3)
C
C
C      COMPUTATION AND STORING IN ARRAYS OF THE LENGTHS OF THE LIMBS
C      AND OF THE DISTANCES BETWEEN THE ORIGINS OF THE LIMBS AND THAT
C      LIMB'S INTERMEDIARY POINT (RESPECTIVELY ''ALONG'' AND ''CLONG'').
C
0162            DO 810 MQ=1,NN
0163            ALONG(MQ) = DSQRT((ARRAY(MQ+1,1)-ARRAY(MQ,1))**2 + (ARRAY(MQ+1,2)
     1   -ARRAY(MQ,2))**2+ (ARRAY(MQ+1,3) - ARRAY(MQ,3))**2)
0164            CLONG(MQ)=DSQRT((ARRAY(MQ+1,1)-ARRAY(MQ,4))**2+(ARRAY(MQ+1,2)-ARR
     1AY(MQ,5))**2 +(ARRAY(MQ+1,3)-ARRAY(MQ,6))**2)
0165     810    CONTINUE
C
C
C
C      THE VALUES ARE GIVEN TO IPECS AFTER TRANSLATION TO SPHERICAL COORDINATES
C
0166            DO 331 MQ=1,NN
0167            XLO=ARRAY(MQ+1,1)-ARRAY(MQ,1)
0168             ARGONE =       ARRAY(MQ+1,2)-ARRAY(MQ,2)
0169            IF(DABS(ARGONE).LT.1D-12.AND.DABS(XLO).LT.1D-12) GO TO 329
0170            ANGLE1 = DATAN2(ARGONE,XLO)
0171            GO TO 330
```

```
0172          329   ANGLE1=0.
0173          330   CONTINUE
0174                YOUPEE=(ARRAY(MO+1,3)-ARRAY(MO,3))/ALONG(MO)
0175               IF(ABS(YOUPEE).GT.1.) YOUPEE=1.
0176                ANGLE2=DARCOS(YOUPEE)
0177                IF(ANGLE1.GE.0.) SIGN=1.
0178                IF(ANGLE1.LT.0.) SIGN=-1.
0179                IPECS( MO  ,1,1) = ANGLE1*(180./PI)+.5*SIGN
0180                IF(ANGLE2.GE.0.) SIGN=1.
0181                IF(ANGLE2.LT.0.) SIGN=-1.
0182                IPECS( MO  ,1,2) = ANGLE2*(180./PI)+.5*SIGN
0183          331   CONTINUE
                C
                C
                C
                C
                C
                C     CONTROL SECTION
                C   CHECKS TO SEE IF LAST LIMB, TIMESTEP OR WHATEVER HAS BEEN REACHED
                C
                C
0184                 DO 41 KLO=1,NN
0185           41    ISTEP(KLO) = ISTEP(KLO) + .1
0186           43   NUMBL = 0
0187                 KT=KT+1
0188           29    NUMBL = NUMBL + 1
0189                IF(NUMBL.GT.NN) GO TO 43
0190                IF(KT.LE.ISTEP(NUMBL))  GO TO 31
0191                 KSW=KSW+1
0192                 IF(KSW.EQ.NN) GO TO 200
0193                 GO TO 29
0194           31    CONTINUE
0195                KSPCF=0
0196                 KTYPN=ITYPE(NUMBL,KT)
```

```
C
C
C       DETERMINATION OF THE CASE INVOLVED, BRANCHING, ETC
C
0197            IF(KTYPA.NE.C) GO TO 9039
0198      56    CONTINUE
0199            XB=ARRAY(NUMBL+1,1)
0200            YB=ARRAY(NUMBL+1,2)
0201            ZB=ARRAY(NUMBL+1,3)
0202            GO TO 39
0203      9039  CONTINUE
0204            IF(KTYPA.EQ.1.OR.KTYPA.EQ.4) GO TO 37
C
C
C
C
C   CASE OF CONICAL MOVEMENT--SETTING UP OF SPECIAL CENTER POINT AND
C
0205            IF(KTYPA.NE.2.AND.KTYPA.NE.5) GO TO 35
0206            TEMP11=ARRAY(NUMBL,1)
0207            TEMP12=ARRAY(NUMBL,2)
0208            TEMP13=ARRAY(NUMBL,3)
C
0209              ARRAY(NUMBL,1)=(ARRAY(NUMBL,4)+ARRAY(NUMBL+1,1))/2.
0210              ARRAY(NUMBL,2)=(ARRAY(NUMBL,5)+ARRAY(NUMBL+1,2))/2.
0211              ARRAY(NUMBL,3)=(ARRAY(NUMBL,6)+ARRAY(NUMBL+1,3))/2.
0212            TEMP1= DSQRT((ARRAY(NUMBL  ,1)-TEMP11)**2+(ARRAY(NUMBL  ,2)-TEMP1
               12)**2+(ARRAY(NUMBL  ,3)-TEMP13)**2)
C
0213            PA=(ARRAY(NUMBL  ,1)-TEMP11)/TEMP1
0214            PB=(ARRAY(NUMBL  ,2)-TEMP12)/TEMP1
0215            PC=(ARRAY(NUMBL  ,3)-TEMP13)/TEMP1
0216            IF(DABS(PA).LT.1.D-12) PA=0.
0217            IF(DABS(PB).LT.1.D-12) PB=0.
0218            IF(DABS(PC).LT.1.D-12) PC=0.
C
C
C
```

```
0219                  X1=ARRAY(NUMBL,1)
0220                  Y1=ARRAY(NUMBL,2)
0221                  Z1=ARRAY(NUMBL,3)
0222                  ARRAY(NUMBL,1) = TEMP11
0223                  ARRAY(NUMBL,2) = TEMP12
0224                  ARRAY(NUMBL,3) = TEMP13
0225                  GO TO 5E76
                C     EQUATION AND PRINTING OF AXIS
                C
                C
                C
                C
                C
                C
0226              35      CONTINUE
                C
                C     CASE OF PURE ROTATION
                C
0227                  IF(KTYPA.NE.3) GO TO 37
0228                    KSIG=KSIG+1
0229                    SIGX(KSIG)=ARRAY(NUMBL+1,1)
0230                    SIGY(KSIG)=ARRAY(NUMBL+1,2)
0231                    SIGZ(KSIG)=ARRAY(NUMBL+1,3)
0232                    TEMP1=ALONG(NUMBL)
0233                    PA=(ARRAY(NUMBL+1,1)-ARRAY(NUMBL,1))/TEMP1
0234                    PB=(ARRAY(NUMBL+1,2)-ARRAY(NUMBL,2))/TEMP1
0235                    PC=(ARRAY(NUMBL+1,3)-ARRAY(NUMBL,3))/TEMP1
0236                  IF(DABS(PA).LT.1.D-12) PA=0.
0237                  IF(DABS(PB).LT.1.D-12) PB=0.
0238                  IF(DABS(PC).LT.1.D-12) PC=0.
0239                  X1=ARRAY(NUMBL  ,1)
0240                  Y1=ARRAY(NUMBL  ,2)
0241                  Z1=ARRAY(NUMBL  ,3)
0242                  XB=ARRAY(NUMBL+1,1)
0243                  YB=ARRAY(NUMBL+1,2)
0244                  ZB=ARRAY(NUMBL+1,3)
0245                GO TO 637
                C
                C
                C
                C
                C
                C     CASE OF PLANAR MOVEMENT
```

```
0246          37      CONTINUE
0247                  X1 = ARRAY(NUMBL    ,1)
0248                  Y1 = ARRAY(NUMBL    ,2)
0249                  Z1 = ARRAY(NUMBL    ,3)
0250        5876      CONTINUE
0251                  X2 = ARRAY(NUMBL+1  ,1)
0252                  Y2 = ARRAY(NUMBL+1  ,2)
0253                  Z2 = ARRAY(NUMBL+1  ,3)
0254                  X3 = ARRAY (NUMBL,4)
0255                  Y3 = ARRAY (NUMBL,5)
0256                  Z3 = ARRAY (NUMBL,6)
              C
              C
              C     EQUATION OF PLANE PASSING THROUGH 1,2,3   EXCEPT FOR STEP 1 OF CON.CASE
              C
0257                  IF(KTYPN.NE.1.AND.KTYPN.NE.4) GO TO 47
0258                  PA =  (Y2-Y1)*(Z3-Z1)  -  (Y3-Y1)*(Z2-Z1)
0259                  PB =  (Z2-Z1)*(X3-X1)  -  (Z3-Z1)*(X2-X1)
0260                  PC =  (X2-X1)*(Y3-Y1)  -  (X3-X1)*(Y2-Y1)
0261                  IF(DABS(PA).LT.1.D-12) PA=0.
0262                  IF(DABS(PB).LT.1.D-12) PB=0.
0263                  IF(DABS(PC).LT.1.D-12) PC=0.
0264          47      CONTINUE
0265                  XTRANS=X2-X1
0266                  YTRANS=Y2-Y1
0267                  ZTRANS=Z2-Z1
0268        637       CONTINUE
0269                  PHI=ANGLE(NUMBL,KT)
0270                  IF(DABS(PA).LT.1D-12.AND.DABS(PB).LT.1D-12) GO TO 53
0271                  PSI=DATAN2(PA,-PB)
0272                  GO TO 54
0273           53     PSI=0.
0274           54     CONTINUE
0275                  DIRC=PC/DSQRT(PA**2+PB**2+PC**2)
0276                  THETA=DARCOS(DIRC)
0277                  IF(KTYPN.EQ.3) GO TO 56
0278                  CALL FINDPT(XTRANS,YTRANS,ZTRANS,PHI,PSI,THETA)
0279                  XB=XTRANS+X1
0280                  YB=YTRANS+Y1
0281                  ZB=ZTRANS+Z1
```

```
C      THE NEW COORDINATES ARE GIVEN TO THE PLOTTING ARRAY ''PLOT''
C      AND ARE GIVEN TO ''ARRAY'' WHERE THEY REPLACE THE FORMER VALUES
C      OF THE LIMB WHOSE NEW EXTREMITY HAS BEEN COMPUTED
C
C282     39   CONTINUE
C
0283           PLOT(NUMBL,KT+1,1) = XB
0284           PLOT(NUMBL,KT+1,2) = YB
C285           PLOT(NUMBL,KT+1,3) = ZB
C
C
0286               ARRAY(NUMBL+1,1) = XB
0287               ARRAY(NUMBL+1,2) = YB
0288               ARRAY(NUMBL+1,3) = ZB
C
C
C
C      THE VALUES ARE TRANSLATED INTO SPHERICAL COORDINATES AND STORED
C      IN THE ARRAY ''IPECS''
C285           XLO = ARRAY(NUMBL+1,1)-ARRAY(NUMBL,1)
C290           ARGONE =         ARRAY(NUMBL+1,2)-ARRAY(NUMBL,2)
C291           IF(DABS(ARGONE).LT.1D-12.AND.DABS(XLO).LT.1D-12) GO TO 1329
0292           ANGLE1 = DATAN2(ARGONE,XLO)
C293           GO TO 1330
0294      1329 ANGLE1=0.
0295      1330 CONTINUE
0296           YOUPEE=(ARRAY(NUMBL+1,3)-ARRAY(NUMBL,3))/ALONG(NUMBL)
C297           IF(DABS(YOUPEE).GT.1.) YOUPEE=1.
0298           ANGLE2=DARCOS(YOUPEE)
C299           IF(ANGLE1.GE.0.) SIGN=1.
0300           IF(ANGLE1.LT.0.) SIGN=-1.
0301           IPECS(NUMBL,KT+1,1)= ANGLE1*(180./PI) +.5 *SIGN
0302           IF(ANGLE2.GE.0.) SIGN=1.
C303           IF(ANGLE2.LT.0.) SIGN=-1.
0304           IPECS(NUMBL,KT+1,2)= ANGLE2*(180./PI) +.5 *SIGN
C305           IF(KTYPE.EQ.0) GO TO 29
C
C
C306      638    CONTINUE
C307           IF(KSPCH.EQ.1) NUMBL=NUMBL+1
0308           IF(NUMBL.GT.NN) GO TO 606
```

```
C
C       ROTATION OF INTERMEDIARY POINTS OF LIMB MOVED AND OF LIGHTER LIMBS
C
0309            DO 601 KYIE=NUMBL,NN
0310            XTRANS=ARRAY(KYIE,4) - X1
0311            YTRANS=ARRAY(KYIE,5) - Y1
0312            ZTRANS=ARRAY(KYIE,6) - Z1
0313            CALL FINDPT(XTRANS,YTRANS,ZTRANS,PHI,PSI,THETA)
0314            ARRAY(KYIE,4) =XTRANS  +X1
0315            ARRAY(KYIE,5) =YTRANS  +Y1
0316            ARRAY(KYIE,6) =ZTRANS  +Z1
0317     601    CONTINUE
C
0318     606  CONTINUE
0319          IF(KSPCH.EQ.1) NUMBL=NUMBL-1

C       ROTATION OF THE SYSTEM OF LIMBS LIGHTER THAN LIMB IN MOVEMENT
C
0320            NZ=NN+1
0321            NY=NUMBL+2
0322            IF(NY.GT.NZ) GO TO 605
0323            DO 602 KYIE=NY,NZ
0324            XTRANS=ARRAY(KYIE,1)-X1
0325            YTRANS=ARRAY(KYIE,2)-Y1
0326            ZTRANS=ARRAY(KYIE,3)-Z1
0327            CALL FINDPT(XTRANS,YTRANS,ZTRANS,PHI,PSI,THETA)
0328            ARRAY(KYIE,1) = XTRANS+X1
0329            ARRAY(KYIE,2) = YTRANS+Y1
0330            ARRAY(KYIE,3) = ZTRANS+Z1
0331     602    CONTINUE
0332     605    CONTINUE
0333            IF(KTYPN.NE.4.AND.KTYPN.NE.5) GO TO 29
0334          ANGLE(NUMBL,KT) =  ROTR(NUMBL,KT)
0335            KTYPN=3
0336          KSPCH=1
0337            GO TO 35
0338     200    KT=KT-1
0339                  KVIEW = KVIEW +1
C
```

```
C
C     SCALING OF ARRAYS FOR PLOTTING
C
0340          SUM = 0.
C341          DO 220 LZ=1,KK
0342    220   SUM = SUM + ALONG(LZ)
0343          IF(ABS(OR1(1)).GE.ABS(OR2(1)).AND.ABS(OR1(1)).GE.ABS(OR3(1))) GO
             1 TO 222
0344          IF(ABS(OR2(1)).GE.ABS(OR3(1))) GO TO 224
0345          SUM = SUM + ABS(OR3(1))
0346          GO TO 207
0347    224   SUM = SUM + ABS(OR2(1))
0348          GO TO 207
0349    222   SUM = SUM + ABS(OR1(1))
0350    207   UNITY = SUM/4.
0351          WRITE( 6,671) UNITY
0352          TS(1)=0.
0353          TS(2)=UNITY
0354          TX(1) = -4.*UNITY
C355          TX(2)=UNITY
C
C     DRAWING OF AXIS
0356          KVIEW = KVIEW - (KVIEW/10)*10
0357          XLIN(1) = 4.  * UNITY
0358          YLIN(1) = 1.0 * UNITY
0359          XLIN(2)= 4.0  * UNITY
C36C          YLIN(2) = 7.0 * UNITY
0361          XLJN(1) = 1.0 * UNITY
0362          YLJN(1) = 4.C * UNITY
0363          XLJN(2) = 7.0 * UNITY
C364          YLJN(2) = 4.C * UNITY
0365          CR1(2) = C.
0366          CR2(2) = C.
0367          CR3(2) = C.
C368          CR1(3) = UNITY
0369              CR2(3) = UNITY
C37C          CR3(3) = UNITY
0371                XTRACE(1) = CR1(1)
C372                YTRACE(1) = CR2(1)
C373                ZTRACE(1) = CR3(1)
C374                KP = KT+1
```

```
0375                KZ=KP+1
0376                 XPLI(KP+1) = XPLI(1)
0377                 YPLI(KP+1) = YPLI(1)
0378                 ZPLI(KP+1) = ZPLI(1)
0379                          XPLI(KP+2) = 0.
0380                          YPLI(KP+2) = C.
0381                          ZPLI(KP+2) = 0.
0382                        XPLI(KP+3) = UNITY
0383                        YPLI(KP+3) = UNITY
0384                        ZPLI(KP+3) = UNITY
0385                 KHCK = KZ/5
0386                          TSA(1)=C.
0387                          TSA(2)=-TS(2)
0388                   SIGX(KSIG+1)=C.
0389                   SIGY(KSIG+1)=0.
0390                   SIGZ(KSIG+1)=C.
0391                   SIGX(KSIG+2)=-UNITY
0392                   SIGY(KSIG+2)= UNITY
0393                   SIGZ(KSIG+2)= UNITY
0394                ALX(1)= -C.5
0395                ALX(2)= -0.5
0396                ALX(3)= 8.5
0397                ALX(4)= 8.5
0398                ALX(5)= -C.5
0399                ALY(1)= -0.5
0400                ALY(2)= 8.5
0401                ALY(3)= 8.5
0402                ALY(4)= -C.5
0403                ALY(5)= -0.5
0404                TM(1)=C.
0405                TM(2)=1.
                 C
                 C    PRINTING RCUTINE
                 C
0406                DO 266 KPL=1,NN
0407                 WRITE(6,876) KPL
0408                 WRITE(6,874)
0409                 DO 199 KH=1,KT
0410                 KE=KH-1
0411                WRITE(6,875) KE,(PLOT(KPL,KH,MPL),MPL=1,3),(IPECS(KPL,KH,MPM),MPM=
                   11,2)
0412          199   CONTINUE
0413          266   CONTINUE
```

```
C
C
C
C       PLOTTING INSTRUCTIONS
C
C
C
0414     478   CALL CCP1PL (1.0,1.0,-3)
0415           IF(KAXIS.EQ.0) GO TO 1480
0416                  GO TO (480,481,482),KVEEW
0417     480   CALL CCP1PL(0.,8.0,-3)
0418                  CALL CCP5AX(C.0,0.0,'Y',1,8.0,0.0,TX)
0419                  CALL CCP5AX(0.0,0.0,'X',1,8.0,270.0,TX)
0420           CALL CCP1PL(0.,-8.,-3)
0421                  GO TO 485
0422     481   CALL CCP1PL( 8.C,0.0,-3)
0423                  CALL CCP5AX(0.0,0.0,'X',1,8.0,180.0,TX)
0424                  CALL CCP5AX(C.0,0.0,'Z',1,8.0,90.0,TX)
0425           CALL CCP1PL(-8.C,0.0,-3)
0426                  GO TO 485
0427     482          CALL CCP5AX(C.0,0.0,'Y',1,8.0,  0.0,TX)
0428                  CALL CCP5AX(0.C,0.0,'Z',1,8.0, 90.0,TX)
0429           GO TO 485
0430     1480  CALL CCP6LN(ALX,ALY,5,1,TM,TM)
0431     485          CONTINUE
0432           CALL CCP6LN(XLJN,YLJN,2,1,TS,TS)
0433           CALL CCP6LN(XLIN,YLIN,2,1,TS,TS)
0434           CALL CCP1PL(4.0,4.C,-3)
C
C     PLOTTING OF TRAJECTORIES
C
0435                  DO 250 KPL=1,NN
0436                  DO 249 MK=1,KP
0437                  XPL1(MK) = PLOT(KPL,MK,1)
0438                  YPL1(MK) = PLOT(KPL,MK,2)
0439                  ZPL1(MK) = PLOT(KPL,MK,3)
0440     249          CONTINUE
0441                  GO TO (280,281,282),KVEEW
0442     280   XPL1(KZ+2)=-UNITY
0443                  CALL LINE (YPL1,XPL1,KZ,1,5,03)
0444           CALL CCP2SY(0.0,-4.2,0.3,103,0.0,-1)
0445           CALL CCP2SY(4.0,C.0,0.3,104,0.0,-1)
0446           IF(KSIG.EQ.0) GO TO 7CC3
0447     7CC3  CONTINUE
```

```
0448                XPL1(KZ+2)= UNITY
0449                DO 290 NLABEL=1,KWDW
0450                MTEMP=NLABEL*5-4
0451                ANBR = NLABEL+.1
0452                XCOOR=YPL1(MTEMP)/UNITY
0453                YCOOR=XPL1(MTEMP)/(-UNITY)
0454                CALL CCP3NR(XCOOR,YCOOR,0.1,ANBR,0.0,-1)
0455          290   CONTINUE
0456                CR1(3)=-UNITY
0457                CR1(3)= UNITY
0458                      GO TO 285
0459          281   XPL1(KZ+2)=-UNITY
0460                      CALL LINE (XPL1,ZPL1,KZ,1,5,03)
0461              CALL CCP2SY(-4.3,-0.5,0.3,103,0.0,-1)
0462              CALL CCP2SY(-0.5,4.0,0.3,105,0.0,-1)
0463               IF(KSIG.EQ.0) GO TO 7001
0464          7001 CONTINUE
0465               XPL1(KZ+2)= UNITY
0466               DO 291 NLABEL=1,KWDW
0467               MTEMP=NLABEL*5-4
0468               ANBR = NLABEL+.1
0469               XCOOR=XPL1(MTEMP)/(-UNITY)
0470               YCOOR=ZPL1(MTEMP)/UNITY
0471               CALL CCP3NR(XCOOR,YCOOR,0.1,ANBR,0.0,-1)
0472          291  CONTINUE
0473               CR1(3)=-UNITY
0474               CR1(3)= UNITY
0475                     GO TO 285
0476          282        CALL LINE (YPL1,ZPL1,KZ,1,5,03)
0477              CALL CCP2SY(4.0,0.0,0.3,104,0.0,-1)
0478              CALL CCP2SY(0.0,4.0,0.3,105,0.0,-1)
0479               IF(KSIG.EQ.0) GO TO 7002
0480          7002 CONTINUE
0481               DO 292 NLABEL=1,KWDW
0482               MTEMP=NLABEL*5-4
0483               ANBR = NLABEL+.1
0484               XCOOR= YPL1(MTEMP)/UNITY
0485               YCOOR=ZPL1(MTEMP)/UNITY
0486               CALL CCP3NR(XCOOR,YCOOR,0.1,ANBR,0.0,-1)
0487          292  CONTINUE
0488          285       CONTINUE
0489          250       CONTINUE
```

```
C
C       PLOTTING OF LINES JOINING DIFFERENT TRAJECTORIES
C
C490                KSPACE=LSPACE
0491                IF(LSPACE.LT.0) KSPACE=-LSPACE
C492                 KMAX=(KT/KSPACE)*KSPACE+1
0493                 IF(KMAX.GT.KT) KMAX=KMAX-KSPACE
C494                 DO 807 KCOU=1,KMAX,KSPACE
0495                IF(LSPACE.LT.0) GO TO 801
C496                        DO 803 NE=1,NN
0497                        XTRACE(NE+1)=PLOT(NE,KCOU,1)
C498                        YTRACE(NE+1)=PLOT(NE,KCOU,2)
0499                        ZTRACE(NE+1)=PLOT(NE,KCOU,3)
C500          803           CONTINUE
C501                        NCC=NN+1
C502                GO TO 802
C503          801   XTRACE(2)=PLOT(NN,KCOU,1)
0504                YTRACE(2)=PLOT(NN,KCOU,2)
C505                ZTRACE(2)=PLOT(NN,KCOU,3)
C506                NCC=2
C507          802   CONTINUE
C508                        GO TO (820,821,822),KVEEW
0509          820           CALL CCP6LN(YTRACE,XTRACE,NCC,1,TS,TSA)
0510                        GO TO 806
C511          821           CALL CCP6LN(XTRACE,ZTRACE,NCC,1,TSA,TS)
C512                        GO TO 806
0513          822           CALL CCP6LN(YTRACE,ZTRACE,NCC,1,TS,TS)
C514          806   CONTINUE
0515          807   CONTINUE
0516          1002  CONTINUE
0517                CALL CCPIPL ( 9.0,-4.59,-3)
0518                IF(KVIEW.LT.10) GO TO 3000
0519                KWCR = KWCR + 1
C520                IF(KWOR.EQ.4) GO TO 3000
C521                KVEEW = KVEEW + 1 - (KVEEW/3)*3
0522                GO TO 478
0523          3000  CONTINUE
0524                 GO TO 19
0525          4502  WRITE(6,655)KC
C526                GO TO 4500
C527          4503  WRITE(6,666) KC
C528          4500  CONTINUE
C529                STOP
C530                END
```

```
0001                SUBROUTINE TRANSL(L,K,R,KANGLE,X,Y,Z,KTEST)
0002                IMPLICIT REAL*8 (A-H,O-Z)
0003          250   FORMAT(32H IMPROPER E-N COORDINATES GIVEN  )
0004                IF((K*KANGLE).GT.180.OR.K.LT.0) GO TO 200
0005                IF(((L+1)*KANGLE).GT.360.OR.L.LT.0) GO TO 200
0006                PI=3.1415926535
0007                 KTEST=0
0008                 IF((180/KANGLE).EQ.K) GO TO 160
0009                 IF(K.EQ.0) GO TO 165
0010                 THETA=360-(L*KANGLE)
0011                 THETA=THETA*(PI/180.)
0012                 PHI=180-(K*KANGLE)
0013                 PHI=PHI*(PI/180.)
0014                 X=R*DSIN(PHI)*DCOS(THETA)
0015                 Y=R*DSIN(PHI)*DSIN(THETA)
0016                 Z=R*DCOS(PHI)
0017                 RETURN
                C    CASE OF NORTH POLE
0018          160    Z=R
0019                 Y=0.
0020                 X=0.
0021                 RETURN
                C    CASE OF SOUTH POLE
0022          165    Z=-R
0023                 Y=0.
0024                 X=0.
0025                RETURN
0026          200   WRITE(6,250)
0027                KTEST=1
0028          201   RETURN
0029                END
```

```
0001            SUBROUTINE FINDPT (HEX,WHY,ZEE,PHI,PSI,THETA)
0002            IMPLICIT REAL*8 (A-H,O-Z)
0003            SPHI=DSIN(PHI)
0004            SPSI=DSIN(PSI)
0005            STHETA=DSIN(THETA)
0006            CPHI=DCOS(PHI)
0007            CPSI=DCOS(PSI)
0008            CTHETA=DCOS(THETA)
0009            TA=HEX
0010            TB=WHY
0011            TC=ZEE
0012            HEX=TA*(CPSI*CPHI-SPSI*CTHETA*SPHI)+TB*(SPSI*CPHI+CPSI*CTHETA*SPH
               1I)+TC* STHETA*SPHI
0013            WHY=TC*STHETA*CPHI-TA*(CPSI*SPHI+SPSI*CTHETA*CPHI)+TB*(CPSI*CTHET
               1A*CPHI-SPSI*SPHI)
0014            ZEE=TA*SPSI*STHETA-TB*CPSI*STHETA+TC*CTHETA
0015            TA=HEX
0016            TB=WHY
0017            TC=ZEE
0018            HEX=TA*CPSI-TB*CTHETA*SPSI+TC*STHETA*SPSI
0019            WHY=TA*SPSI+TB*CTHETA*CPSI-TC*STHETA*CPSI
0020            ZEE=TB*STHETA+TC*CTHETA
0021            RETURN
0022            END
```

APPENDIX Ic. SAMPLE PLOTS OF DANCER

Ic-1. A one limb case where:

The first limb describes one fourth of a vertical counter clockwise circle for 20 timesteps then describes one-half of a cone for 20 more timesteps.

In E-W notation:

$$1 = 45°$$

$$\binom{6}{2} \;||\; \binom{0}{4}_{2\downarrow} \;||\; \binom{\hat{6}}{3}_{4}$$



Ic-1.1. X-Z projection.



Ic-1.2. Y-Z projection.



Ic-1.3. X-Y projection.

Ic-2. A two limb case where:

The first limb describes a counter clockwise cone with $\binom{4}{3}$ and $\binom{0}{3}$ as diameter extremities, while rotating on itself clockwise by 360°

The second limb has no movement of its own.

In E-W notation

$$l = 45°$$

$$\binom{4}{3} \Big\| \binom{\hat{0}}{3}\ 4\ \widehat{8}$$

$$\binom{6}{2} \Big\| \binom{6}{2}$$

The position is indicated for every 5 timesteps (normal line density).



Ic-2.1. X-Z projection.



Ic-2.2. X-Y projection.

Ic-3. A two limb case where:

The first limb describes a counter clockwise cone with diameter extremities $\binom{0}{3}$ and $\binom{4}{3}$, while rotating on itself counter clockwise by 360°.

The second limb has no movement of its own.

In E-W notation

$$1 = 45°$$

$$\begin{matrix} \binom{6}{3} & \| & \binom{\hat{0}}{3} \; 4 \; \underline{8} \\ \binom{6}{2} & \| & \binom{6}{2} \end{matrix}$$

The position is indicated for every 5 timesteps (normal line density).



Ic-3.1. X-Z projection.



Ic-3.2. X-Y projection.

Ic-4. A two limb case where:

The first limb describes a counter clockwise horizontal circle.

The second limb describes three counter clockwise circles.

In E-W notation

$$1 = 45°$$

$$\binom{6}{2} \Big\| \; 8\updownarrow$$

$$\binom{0}{4} \Big\| \; 24\uparrow$$

The position is indicated for every 2 timesteps (half of maximum line density).



Ic-4.1. X-Z projection.



Ic-4.2. Y-Z projection.



Ic-4.3. X-Y projection.

Ic-5. A two limb case where:

The first limb describes half a counter clockwise circle passing through $\binom{2}{3}$ and $\binom{4}{2}$.

The second limb describes a counter clockwise cone with diameter extremities $\binom{1}{3}$ and $\binom{6}{3}$.

In E-W notation

$$1 = 45°$$

$$\binom{4}{2} \;\|\| \; \binom{2}{3} \; \underline{\lfloor 4}$$

$$\binom{6}{3} \;\|\| \; \binom{\hat{1}}{3} \; \underset{\smile}{8}$$

The position is indicated for every timestep (maximum line density).



Ic-5.1. X-Z projection.



Ic-5.2. Y-Z projection.



Ic-5.3. X-Y projection.

Ic-6. A three limb case where:

The first limb describes a third of a counter clockwise horizontal circle.

The second limb describes a fourth of a circle while rotating on itself.

The third limb has no movement of its own.

In E-W notation:

$$l = 45°$$

$$\begin{matrix} \binom{6}{2} & \| & \binom{4}{2}\ \underset{\rightarrow}{2} \\ \binom{0}{4} & \| & \binom{6}{2}\ \underline{2}\rfloor \\ \binom{6}{2} & \| & \binom{6}{2} \end{matrix}$$

Maximum line density.



Ic-6.1. X-Z projection.



Ic-6.2. Y-Z projection.



Ic-6.3. X-Y projection.

Ic-7. A three limb case where:

The first limb describes half of a horizontal counter clockwise circle while rotating on itself counter clockwise by 360°

The second limb describes a third of a vertical circle while rotating on itself clockwise by 180°.

The third limb describe a quarter of a circle.

In E-W notation

$$1 = 45°$$

$$\begin{pmatrix} 2 \\ 2 \end{pmatrix} \Big\| \; \underset{\rightarrow}{4} \; \overset{\curvearrowleft}{8}$$

$$\begin{pmatrix} 2 \\ 2 \end{pmatrix} \Big\| \; 2\downarrow \; \overset{\frown}{4}$$

$$\begin{pmatrix} 2 \\ 2 \end{pmatrix} \Big\| \; 2\uparrow$$

Maximum line density.



Ic-7.1. X-Z projection.



Ic-7.2. X-Y projection.

Ic-8. A three limb case where:

The first limb describes half a cone for 72 timesteps.

The second limb describes one fourth of a circle for 36 timesteps.

The third limb describes three fourths of a cone for 36 timesteps.

In E-W notation

$$1 = 45°$$

$$\begin{matrix} \binom{6}{2} & \| & \binom{\hat{5}}{2} & 2 & \| & \hat{2} \\ \binom{0}{4} & \| & \binom{6}{2} & 2 & & \\ \binom{0}{4} & \| & \binom{\hat{7}}{1} & 7 & & \end{matrix}$$

Maximum line density.



Ic-8.1. X-Z projection.



Ic-8.2. Y-Z projection.



Ic-8.3. X-Y projection.

APPENDIX IIa. SAMPLE PROGRAM FOR STKMAN

(WALK PROGRAM)

```
      DIMENSION BOD(5,4),CS(5,4,3 ),RP(3),R(5,5,3)                      00010
      RP(1)=0.                                                          00020
      RP(2)=0.                                                          00030
      RP(3)=0.                                                          00040
      TIME=0.                                                           00050
      KT=0                                                              00060
      T1=1.                                                             00070
      S=4.                                                              00080
      N=2                                                               00090
      CALL CCP1PL(0.1,0.1,-3)                                           00100
      CALL BODY(BOD)                                                    00110
      CALL ZERO(CS)                                                     00120
   50 CONTINUE                                                          00130
      T=TIME                                                            00140
            CALL WALK(T,T1,S,N,CS)                                      00150
      CALL POSIT(RP,CS,BOD,R)                                           00160
      CALL POTT(R,RP,KT)                                                00170
      KT=KT+1                                                           00180
      TIME=TIME+0.05                                                    00190
      IF(TIME.GT.2.) GO TO 1000                                         00200
      GO TO 50                                                          00210
 1000 STOP                                                              00220
      END                                                               00230
```

```
      SUBROUTINE WALK(T,T1,S,N,CS)                                      00240
      DIMENSION CS(5,4,3)                                               00250
      PI=3.1415926                                                      00260
      IF(T.GT.0.) GO TO 20                                              00270
      EN=N                                                              00280
      S1=1.5                                                            00290
      S2=1.5                                                            00300
      S3=3.0                                                            00310
      H=SQRT(S3**2 - ((S/2)**2))                                        00320
      DEL=S/8.                                                          00330
   15 PHI1=0.                                                           00340
      TH1=0.                                                            00350
      PHI2=0.                                                           00360
      TH2=0.                                                            00370
      GO TO 1000                                                        00380
   20 TEMP=T1/2.                                                        00390
      IF(T.GT.TEMP) GO TO 40                                            00400
      TAU=T/T1                                                          00410
      XR=-S*TAU                                                         00420
      ZR=S3+ (H-S3)*(2*TAU)**2                                          00430
      CALL ANGLE(XR,ZR,PHI1,TH1)                                        00440
      XL=-XR                                                            00450
      ZL=ZR-8.*DEL*TAU*(.5-TAU)                                         00460
      CALL ANGLE(XL,ZL,PHI2,TH2)                                        00470
      GO TO 1000                                                        00480
   40 TEMP=(EN-.5)*T1                                                   00490
      IF(T.GE.TEMP) GO TO 80                                            00500
      M=(2.*(T/T1)+1.)/2.                                               00510
      EM=M                                                              00520
      TAU=(T-(2.*EM-1.)*T1/2.)/T1                                       00530
      Z=H                                                               00540
      X=(S*(1.-2.*TAU))/2.                                              00550
      CALL ANGLE(X,Z,PHI,TH)                                            00560
      Z=Z-4.*DEL*TAU*(1.-TAU)                                           00570
```

```
      X=-X                                                              00580
      CALL ANGLE(X,Z,XI,ETA)                                            00590
      IF((M-(M/2)*2).EQ.1) GO TO 70                                     00600
   60 CONTINUE                                                          00610
      PHI1=PHI                                                          00620
      TH1=TH                                                            00630
      PHI2=XI                                                           00640
      TH2=ETA                                                           00650
      GO TO 1000                                                        00660
   70 PHI1=XI                                                           00670
      TH1=ETA                                                           00680
      PHI2=PHI                                                          00690
      TH2=TH                                                            00700
      GO TO 1000                                                        00710
   80 IF(T.GE.(EN*T1)) GO TO 15                                         00720
      TAU=(T-(EN-.5)*T1)/T1                                             00730
   90 Z=H+ (S3-H)*(2.*TAU)**2                                           00740
      X=(S*(1.-2.*TAU))/2.                                              00750
      CALL ANGLE(X,Z,PHI,TH)                                            00760
      Z=Z-8.*DEL*TAU*(.5-TAU)                                           00770
      X=-X                                                              00780
      CALL ANGLE(X,Z,XI,ETA)                                            00790
      IF(N.GT.((N/2)*2)) GO TO 70                                       00800
      GO TO 60                                                          00810
 1000 CS(2,2,2) = PHI1                                                  00820
      CS(2,3,1) = TH1                                                   00830
      CS(2,4,1) = PI/2. - PHI1 + TH1                                    00840
      CS(3,2,2) = PI - PHI2                                             00850
      CS(3,3,1) = TH2                                                   00860
      CS(3,4,1) =-PHI2 + TH2 + PI/2.                                    00870
      RETURN                                                            00880
      END                                                               00890
```

```
      SUBROUTINE ANGLE(X,Z,PHI,TH)                                    00900
      CTH = (X**2 + Z**2 - 4.5)/4.5                                   00910
      TH=ARCOS(CTH)                                                   00920
      STH=SIN(TH)                                                     00930
      T1= X*(1.+CTH)+Z*STH                                            00940
      T2= Z*(1.+CTH) - X*STH                                          00950
      PHI=ATAN2(T1,T2)                                                00960
      RETURN                                                          00970
      END                                                             00980
```

```
      SUBROUTINE BODY(BOD)                                            00990
      DIMENSION BOD(5,4)                                              01000
      BOD(1,1) = 0.5                                                  01010
      BOD(1,2) = 1.5                                                  01020
      BOD(1,3) = .25                                                  01030
      BOD(1,4) = .75                                                  01040
      DO 10 K=2,3                                                     01050
      BOD(K,1) = .5                                                   01060
      BOD(K,2) = 1.5                                                  01070
      BOD(K,3) = 1.5                                                  01080
      BOD(K,4) = 0.5                                                  01090
10    CONTINUE                                                        01100
      DO 20 L=4,5                                                     01110
      BOD(L,1) = .75                                                  01120
      BOD(L,2) = 1.                                                   01130
      BOD(L,3) = 1.                                                   01140
      BOD(L,4) = 0.5                                                  01150
20    CONTINUE                                                        01160
      RETURN                                                          01170
      END                                                             01180
```

```
      SUBROUTINE ZERO(R)                                                01190
      DIMENSION R(5,4,3)                                                01200
      PI=3.1415926                                                      01210
      DO 10 KK=1,5                                                      01220
      DO 10 KL=1,4                                                      01230
      DO 10 KM=1,3                                                      01240
   10 R(KK,KL,KM)=0.                                                    01250
      R(2,1,1) = PI/2.                                                  01260
      R(2,2,1) = PI/2.                                                  01270
      R(2,3,2) = (3.*PI)/2.                                             01280
      R(2,3,3) =PI/2.                                                   01290
      R(2,4,1) = PI/2.                                                  01300
      R(2,4,2) = PI/2.                                                  01310
      R(3,1,1) = PI/2.                                                  01320
      R(3,1,2) = PI                                                     01330
      R(3,1,3) = PI                                                     01340
      R(3,2,1) = PI/2.                                                  01350
      R(3,2,2) = PI                                                     01360
      R(3,2,3) = PI                                                     01370
      R(3,3,2) = (3.*PI)/2.                                             01380
      R(3,3,3) =PI/2.                                                   01390
      R(3,4,1) = PI/2.                                                  01400
      R(3,4,2) = PI/2.                                                  01410
      R(4,1,1) = PI/2.                                                  01420
      R(4,2,1) = PI/2.                                                  01430
      R(5,1,1) = PI/2.                                                  01440
      R(5,1,2) = PI                                                     01450
      R(5,1,3) = PI                                                     01460
      R(5,2,1) = PI/2.                                                  01470
      R(5,2,2) = PI                                                     01480
      R(5,2,3) = PI                                                     01490
      RETURN                                                            01500
      END                                                               01510
```

```
      SUBROUTINE POSIT(RP,CS,BOD,R)                                      01520
      DIMENSION RP(3),CS(5,4,3),BOD(5,4),R(5,5,3),A(3,3),B(3,3),C(3,3),  01530
     1  TB(3,3)                                                          01540
      DO 160 K=1,5                                                       01550
      IF(K-3)10,10,60                                                    01560
   10 DO 20 I=1,3                                                        01570
   20 R(K,1,I)=RP(I)                                                     01580
      DO 50 N=1,3                                                        01590
      DO 50 M=1,3                                                        01600
      IF(N-M)30,40,30                                                    01610
   30 B(N,M)=0.                                                          01620
      GO TO 50                                                           01630
   40 B(N,M)=1.                                                          01640
   50 CONTINUE                                                           01650
      GO TO 90                                                           01660
   60 DO 70 I=1,3                                                        01670
   70 R(K,1,I)=R(1,3,I)                                                  01680
      DO 80 N=1,3                                                        01690
      DO 80 M=1,3                                                        01700
   80 B(N,M)=TB(N,M)                                                     01710
   90 DO 160 J=2,5                                                       01720
      L=J-1                                                              01730
      THETA=CS(K,L,1)                                                    01740
      PHI=CS(K,L,2)                                                      01750
      PSI=CS(K,L,3)                                                      01760
      CALL ORIENT(A,THETA,PHI,PSI)                                       01770
      DO 100 N=1,3                                                       01780
      DO 100 M=1,3                                                       01790
      C(N,M)=0.                                                          01800
      DO 100 NS=1,3                                                      01810
  100 C(N,M)=C(N,M)+B(N,NS)*A(NS,M)                                      01820
      DO 110 N=1,3                                                       01830
      DO 110 M=1,3                                                       01840
  110 B(N,M)=C(N,M)                                                      01850
      IF(K-1)150,120,150                                                 01860
  120 IF(J-3)150,130,150                                                 01870
  130 DO 140 N=1,3                                                       01880
      DO 140 M=1,3                                                       01890
  140 TB(N,M)=B(N,M)                                                     01900
  150 DO 160 I=1,3                                                       01910
  160 R(K,J,I)=R(K,J-1,I)+BOD(K,L)*B(I,3)                                01920
      RETURN                                                             01930
      END                                                                01940
```

```
      SUBROUTINE ORIENT(A,THETA,PHI,PSI)                                01950
      DIMENSION A(3,3)                                                  01960
      CTHETA=COS(THETA)                                                 01970
      STHETA=SIN(THETA)                                                 01980
      CPHI=COS(PHI)                                                     01990
      SPHI=SIN(PHI)                                                     02000
      CPSI=COS(PSI)                                                     02010
      SPSI=SIN(PSI)                                                     02020
      A(1,1)=CPSI*CPHI-CTHETA*SPHI*SPSI                                 02030
      A(1,2)=-SPSI*CPHI-CTHETA*SPHI*CPSI                                02040
      A(1,3)=STHETA*SPHI                                                02050
      A(2,1)=CPSI*SPHI+CTHETA*CPHI*SPSI                                 02060
      A(2,2)=-SPSI*SPHI+CTHETA*CPHI*CPSI                                02070
      A(2,3)=-STHETA*CPHI                                               02080
      A(3,1)=STHETA*SPSI                                                02090
      A(3,2)=STHETA*CPSI                                                02100
      A(3,3)=CTHETA                                                     02110
      RETURN                                                            02120
      END                                                               02130
```

```
      SUBROUTINE PRINT (R)                                              02140
      DIMENSION R(5,5,3)                                                02150
  100 FORMAT (3F7.3,2X,3F7.3,2X,3F7.3,2X,3F7.3,2X,3F7.3/  )             02160
      WRITE(6,100) (((R(K,L,M),M=1,3),L=1,5),K=1,5)                     02170
      RETURN                                                            02180
      END                                                               02190
      SUBROUTINE POTT(R,RP,KT)                                          02200
      DIMENSION X(7),Y(7),Z(7),R(5,5,3),RP(3)                           02210
      X(6) = 0.                                                         02220
      Y(6) = 0.                                                         02230
      Z(6) = 0.                                                         02240
      X(7) = 2.5                                                        02250
      Y(7) = 2.5                                                        02260
      Z(7) = 2.5                                                        02270
      AI=KT+.1                                                          02280
      CALL CCP3NR(1.2,.2,0.35,AI,0.0,-1)                                02290
      CALL CCP1PL(1.5,7.33,-3)
      DO 1053 KSQ=1,5                                                   02310
      DO 1052 KJO=1,5                                                   02320
      X(KJO) = R(KSQ,KJO,1) - RP(1)                                     02330
      Y(KJO) = R(KSQ,KJO,2) - RP(2)                                     02340
      Z(KJO) = R(KSQ,KJO,3) - RP(3)                                     02350
 1052 CONTINUE                                                          02360
      CALL LINE(X,Z,5,1,1,03)                                           02370
      CALL CCP1PL(0.0,-3.0,-3)                                          02380
      CALL LINE(Y,Z,5,1,1,03)                                           02390
      CALL CCP1PL(0.0,-3.0,-3)                                          02400
      CALL LINE(X,Y,5,1,1,03)                                           02410
      CALL CCP1PL(0.0, 6.0,-3)                                          02420
 1053 CONTINUE                                                          02430
      CALL CCP1PL(0.5,-7.33,-3)                                         02440
      RETURN                                                            02450
      END                                                               02460
```

APPENDIX IIb. SAMPLE PLOTS FOR STKMAN

BLANK PAGE







28 29 30 31



16 17 18 19





12 13 14 15


0
1
2
3







4 5 6 7







8 9 10 11



20 21 22 23





24 25 26 27

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)

University of Illinois
Biological Computer Laboratory
Urbana, Illinois 61801

2a. REPORT SECURITY CLASSIFICATION

UNCLASSIFIED

2b. GROUP

3. REPORT TITLE

NOTATION OF MOVEMENT

4. DESCRIPTIVE NOTES (Type of report and inclusive dates)

scientific; ; final

5. AUTHOR(S) (Last name, first name, initial)

Eshkol, Noa; Melvin, Peter; Michl, Jean; Von Foerster, Heinz; Wachmann, Abraham

6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
February 15, 1970	167	11

8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)
DA-ARO-D-31-124-G998	Final Report (DA-ARO)
b. PROJECT AND TASK NO. 7875-RT	
c.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)
d.	

10. AVAILABILITY/LIMITATION NOTICES

Distribution of this document is unlimited.

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY
	Army Research Office-Durham Box CM, Duke Station Durham, North Carolina 27706

13. ABSTRACT

First, the basic principles of a notation of bodily movements as developed by Noa Eshkol and Abraham Wachmann are summarized. The syntactic elements of this notation are then translated into equations of motion in a set of Cartesian coordinate systems each of which is associated with a movable part of the body. Hence, by a cascade of transforms, any desired (and executable) movement is now describable. A computer program has been written which carries out these transformations, thus, any movement prescribed by a sequence of symbols in Eshkol-Wachmann notation can now be represented by the appropriate trajectories which, in this program, are printed out with a CALCOMP plotter as projections into the three principal planes, the XY-plane, the YZ-plane and the ZX-plane. Numerous illustrations exemplify the rich possibilities of an algorithm which translates symbolic commands into effective movements.

DD FORM 1 JAN 64 1473

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Body Movements Notation Movement Notation Translation Algorithms for Movements Computer Representation of Movements Kinematic Models of Body Movements						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization *(corporate author)* issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers *(either by the originator or by the sponsor)*, also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through

_____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through

_____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through

_____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring *(paying for)* the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as *(TS), (S), (C),* or *(U).*

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification

END

DATE

FILMED

5-14-70